

OPTIONAL EQUIPMENT & FEATURES

INTERIOR

UTQ	CONTENT THEFT ALARM DISABLE - Flashing lamps and horn warning disable (To avoid inadvertent alarm activation this option is recommended for customers that do not intend on using keyless entry remote fobs)
B30	FLOOR COVERING - Color keyed carpeting (includes rear cargo floor)
B58	FLOOR MATS - Color keyed carpeted front and 2nd row included and only available with B30 Floor Covering (not available with vinyl floor covering)
VAV	FLOOR MATS - All weather (Dealer Installed) Requires (B30) floor covering
6E2	KEY COMMON - All vehicles in fleet, provides a single key cut with a specific code that is common to the door lock and ignition of all the vehicles in the vehicle fleet; this key code is an alternate to SEO 6E8 key common, complete vehicle fleet; An unlimited number of ignition keys may be programmed to a vehicle. Not compatible with Caprice or Impala. Not compatible with 2014 or older Tahoe.
6E8	KEY COMMON - All vehicles in fleet, provides a single key cut with a specific code that is common to the door lock and ignition of all the vehicles in the vehicle fleet; this key code is an alternate to SEO 6E2 key common, complete vehicle fleet; An unlimited number of ignition keys may be programmed to a vehicle. Not compatible with Caprice or Impala. Not compatible with 2014 or older Tahoe.
AVM	KEYLESS ENTRY TRANSMITTERS - Fleet Package includes 6 additional transmitters. Transmitters are not programmed. Each transmitter, including the two standard with the vehicle, must be programmed together by the customer or a dealer at customer expense. Transmitter programming is not a warranty item. See illustration section for programming remote key transmitter instructions. Vehicle specific common fleet transmitter frequency is not available.
5HP	KEYS - 6 additional, keys are not programmed to vehicle. Each key, including the 2 delivered with the vehicle, must be programmed at the same time by the customer or a dealer at customer expense. Key programming is not a warranty item. A maximum of 8 random code keys can be programmed. If a key is lost, all remaining keys must be reprogrammed with the replacement key. See illustration section for key programming instructions.
6E7	LAMP, AUXILIARY DOME - Red and white auxiliary dome lamp is located on the headliner between front row seats (red is LED, white is INCANDESCENT) (wired independently from standard dome lamp)
UE0	ONSTAR DELETE - BLUETOOTH CELL PHONE CONNECTIVITY, COMPASS AND WI-FI ARE DELETED WHEN ORDERED (not recommended)
ROV	ONSTAR WITH 4G LTE FOR FLEET - 12GB/12 months, provides a built-in Wi-Fi hotspot to connect to the internet at 4G LTE speeds, includes AT&T 12GB data plan good for 12 months. Requires (UE1) OnStar and (VV4) OnStar with 4G LTE and one of the following order types: FLS, FNR, FRC, FBC, FGO or FEE. Not available with ROW. Visit www.onstar.com for vehicle availability, details and system limitations. Services and connectivity may vary by model and conditions. 4G LTE service available in select markets. 4G LTE performance based on industry averages and vehicle systems design. Some services require data plan.
ROW	ONSTAR WITH 4G LTE FOR FLEET - 24GB/24 months, provides a built-in Wi-Fi hotspot to connect to the internet at 4G LTE speeds, includes AT&T 24GB data plan good for 24 months. Requires (UE1) OnStar and (VV4) OnStar with 4G LTE and one of the following order types: FLS, FNR, FRC, FBC, FGO or FEE. Not available with ROV. Visit www.onstar.com for vehicle availability, details and system limitations. Services and connectivity may vary by model and conditions. 4G LTE service available in select markets. 4G LTE performance based on industry averages and vehicle systems design. Some services require data plan.
JF4	PEDALS - Power-adjustable for accelerator and brake
6N6	REAR DOOR LOCKS AND HANDLES INOPERATIVE - Rear power locks are inoperable at rear door but operate from drivers position, rear doors can be opened only from outside
6N5	REAR DOOR WINDOW SWITCHES INOPERATIVE - Rear windows only operate from drivers position
V76	RECOVERY HOOKS - Two black front frame-mounted, recommended if front push bumper is to be installed (required on all models sold to Alaska, Guam, Hawaii, Puerto Rico and Virgin Islands)
8T1	REMOTE VEHICLE STARTER SYSTEM - Includes remote keyless entry
9U3	SEAT FRONT CENTER - Front center seat (20% seat) delete, Power driver and passenger bucket seats in base cloth trim. Derived from RPO (AZ3) 40-20-40 split bench seat with the 20% section removed. Does not include a floor console. All exposed floor area will remain untrimmed. Not available with (A95) Bucket Seats. Requires (HOU) Jet Black trim.
A95	SEAT & CENTER CONSOLE - Driver and Passenger Front Bucket Cloth Seats with integrated retail console, 10-way Power Driver and Passenger Seats with Outboard Seat Back, Pelvic Airbag and Driver, Inboard Seat Back Airbag. Not recommend for vehicles intended to be up-fitted with aftermarket equipment.
5T5	SEAT - Front cloth with vinyl rear seat (see front seats and interior trim illustration page for description)
VRS	SHADE - Rear cargo (Dealer Installed)
TGK	SPECIAL PAINT SOLID - One color all normally body-colored non-sheet metal parts will be gloss Black. This includes front and rear facias, liftgate handle and applique, D-pillars and upper liftgate applique. Mirrors and door handles will be grained Black parts. B85 body-side moldings are not available except with SEO option 5T4 exterior body-colored parts. Required with any SEO paint selection (may require extended lead time)

AVAILABLE EXTERIOR COLORS *Actual colors may vary*

6WT Champagne Silver Metallic	6AN Silver Ice Metallic	6BN Black	6WX Brownstone Metallic	6KG Jungsten Metallic	6AZ Summit White	61C Slate Grey Metallic	61E Sierra Red Tintcoat	67U Sage Metallic
---	-----------------------------------	---------------------	-----------------------------------	---------------------------------	----------------------------	-----------------------------------	-----------------------------------	-----------------------------

Additional options

SEO PAINT AVAILABLE

COLOR DESCRIPTION	SEO CODE	WA#
Blue ^{1, 2}	9V2	WA-9618
Woodland Green	9V5	WA-9615
Victory Red ²	5T4	WA-9233
Yellow		WA-9414
Wheatland Yellow (86U)	9W3	WA-258A
Dark Toreador Red		WA
Dark Blue Metallic ^{1, 2} (25U)	9V7	WA-7921

1 - Includes two openings in front fascia. Recovery hooks (V76) recommended for customers not installing after-market push bars.
2 - See standard equipment illustrations section

AVAILABLE INTERIOR COLOR *Actual colors may vary*

H00 Black Cloth	H0U Black Vinyl
---------------------------	---------------------------

POWERTRAIN

ENGINE				TRANSMISSION		AXLE	
OPTION CODE	TYPE	DISPLACEMENT LITERS/CU. IN.	FUEL SYSTEM	OPTION CODE	TYPE	OPTION CODE	RATIO
L83	V8	5.3/325	Active fuel management FlexFuel ¹ (gas or E85 ethanol)	MXO/MYC	6L80 6-speed auto. with OD	GU4	3.08

EMISSIONS - MUST BE SPECIFIED

FE9	FEDERAL EMISSIONS. Federal requirements
YF5	CALIFORNIA EMISSIONS. California state requirements
NE1	CT/DE/ME/MD/MA/NJ/NY/OR/PA/RI/VT/WA EMISSIONS. Connecticut, Delaware, Maine, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island, Vermont and Washington state requirements
NB8	EMISSIONS OVERRIDE. California (allows a dealer in states that require California emissions - California, Connecticut, Delaware, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island or Washington - to order Federal emissions for a vehicle that will be registered in a state that has Federal emission requirements). Do not use for vehicles that will be registered in California, Connecticut, Delaware, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island or Washington. Requires (FE9) Federal emissions requirements. Not available in Maine or Vermont.
NB9	EMISSIONS OVERRIDE. State-specific (for dealers ordering vehicles in (YF5) or (NE1) emission states - California, Connecticut, Delaware, Maine, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island, Vermont and Washington). Allows a California dealer (YF5 emissions) to order (NE1) emissions with (NB9) emissions override code for registration in (NE1) states; or, a Connecticut, Delaware, Maine, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island, Vermont and Washington dealer (NE1 emissions) to order (YF5) emissions with (NB9) emissions override code for registration in California.
NC7	NC7 EMISSIONS OVERRIDE. Federal (for vehicles ordered by dealers in Federal emission states with (YF5) or (NE1) emissions - Not required for vehicles being shipped to California, Connecticut, Delaware, Maine, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island, Vermont or Washington) Requires (YF5) California state emissions requirements or (NE1) Connecticut, Delaware, Maine, Massachusetts, New York, Pennsylvania, Rhode Island or Vermont state emissions requirements
NOTE:	2016 Tahoe EPA Engine family test group is GGMXT05.3382

STANDARD TIRES S-SPEED RATED

MANUFACTURER	QUANTITY	SIZE	SPEED RATING	TYPE
Random	5	P255/70R17	S	All season BW

NOTE: Due to specific requirements for performance durability and safety, GM recommends only the original equipment tires for replacement
 Tire Plies = Tread: 2 Polyester, 2 Steel, 2 Nylon Sidewall; 2 Polyester Total 8 Ply

Tire Chains - If the vehicle has 265/65R18, P265/65R18, P275/55R20, or P285/45R22 size tires, do not use tire chains. There is not enough clearance. Tire chains used on a vehicle without the proper amount of clearance can cause damage to the brakes, suspension, or other vehicle parts. The area damaged by the tire chains could cause loss of control and a crash. Use another type of traction device only if its manufacturer recommends it for the vehicle's tire size combination and road conditions. Follow that manufacturer's instructions. To avoid vehicle damage, drive slow and readjust or remove the traction device if it is contacting the vehicle. Do not spin the wheels. If traction devices are used, install them on the rear tires. If the vehicle has P255/70R17 or P265/70R17 size tires, use tire chains only where legal and only when necessary. Use chains that are the proper size for the tires. Install them on the rear tires only. Do not use chains on the front tires. Tighten them as tightly as possible with the ends securely fastened. Drive slowly and follow the chain manufacturer's instructions. If the chains contact the vehicle, stop and retighten them. If the contact continues, slow down until it stops. Driving too fast or spinning the wheels with chains on will damage the vehicle.

1. E85 is 85% ethanol and 15% gasoline.

STANDARD 5W4 CHASSIS FEATURES

AIR CLEANER	High-capacity
ALTERNATOR	170-amp high output with idle boost based on battery energy level (see specifications page for description)
AXLE	3.08 Ratio with heavy-duty locking differential
BATTERIES	Primary 720 CCA, 80 amp-hour rating with battery rundown protection (may be configured to protect customer installed equipment). Auxiliary 730 CCA, 70 amp-hour battery without battery run-down protection for customer installed equipment (see specifications page)
COOLING	Heavy-duty high-capacity radiator, electric fans and extended life coolant; coolant hoses are EPDM (ethylene-propylene-diene monomer) rubber; silicone hoses are not required (coolant is DEX-COOL good for 5 years/150,000 miles, protects from -34° F to +265° F and against rust and corrosion)
ENGINE	5.3L EcoTec3 V8 with direct injection, variable valve timing (VVT), Active Fuel Management (AFM), aluminum block, and FlexFuel capability (gasoline or E85 ¹ ethanol); top speed 112 mph; includes air conditioning wide open throttle cut off (see specifications page)
FRAME	Full perimeter, modular with hydroformed rails (includes ground straps)
FUEL TANK CAPACITY	26 gallon (98 liters)
HILL START ASSIST	This feature is designed to prevent the vehicle from rolling, either forward or rearward, during vehicle drive off.
OIL COOLERS	Engine oil, oil-to-coolant heat exchanger in passenger side of coolant radiator. Transmission oil, oil-to-coolant heat exchanger in driver side of coolant radiator with auxiliary transmission air-to-oil cooler in upper portion of the AC condenser (see illustration section for description).
PROP SHAFT	4 inch diameter aluminum
RADIO SUPPRESSION	Grounding straps, at five locations (see illustration section for location)
REAR DIFFERENTIAL	Heavy-duty locking
SPARK PLUGS	Extended life - iridium tip
STABILITRAK	An advanced computer controlled stability enhancement system assists the driver with directional control of the vehicle in difficult driving conditions. (See illustration section for Stabilitrak button location and Stabilitrak page for description)
STEERING	Electric power-assisted rack and pinion (see illustrations section for description)
SUSPENSION, FRONT	Coil-over-shock with stabilizer bar
SUSPENSION, REAR	Multi-link with coil springs with stabilizer bar
TIRES	All-season P255/70R17 blackwall (see optional equipment page for additional tire and wheel options)
TIRE PRESSURE MONITOR	Check tire pressure will display in driver message center; also displays individual tire pressure (see illustrations section for description)
TIRE, SPARE	Full-size spare, lockable with outside winch-type carrier mounted under frame at rear (TPM sensor not included).
TRAILERING EQUIPMENT	SAE Class II hitch. Trailer may weigh up to 6,300 pounds with proper hitch selection. 8,400 lb Max Trailering Package (NHT) optional. See the Owners Manual for additional information.
TRANSMISSION	Enhanced calibration 6-speed automatic with overdrive and tow/haul mode. Electronically-controlled transmission provides protection against over-revving the engine in low gear and a mechanical low gear blockout is not required; if a driver manually selects low gear and falls to manually upshift to high gear, the powertrain control module automatically protects the drivetrain.
TRANSFER CASE	Autotrac, 2-speed electronic with rotary control, includes neutral position for dinghy towing (2HI, 4AUTO, 4HI, 4LO, and Neutral setting) See owners manual procedure for shifting into N (Neutral) and shifting out of N (Neutral).
UNDER BODY SHIELD, FRONT	Two piece heavy-duty aluminum front underbody shield starting behind front bumper and running to 2nd cross-member protecting front underbody and oil pan (see illustrations section for description)
WARRANTY	See Maintenance and Warranty section for description
WHEELS	17" Grey finished steel wheel
WHEEL CENTER CAP	Argent plastic

1. E85 is 85% ethanol and 15% gasoline.

STANDARD 5W4 EXTERIOR FEATURES	
ASSIST STEPS	Black, mounted between front and rear wheels
BODY SIDE MOLDINGS	Optional (see available options page)
DEFOGGER	Electric, rear window
DOOR HANDLES	Body color
DOOR LOCKS	Power, programmable with lockout protection and automatic locking/unlocking. Door locks can be programmed via radio settings menu (see standard equipment illustrations section). Lock cylinder not available on passenger front door or rear liftgate. Child safety door and window locks individually controlled electronically by driver door mounted switches. Includes 2 remote transmitters.
FASCIA, FRONT	Body color with police specific lower extension for increased brake cooling and ground clearance
FASCIA, REAR	Body color with step pad
FOG LAMPS	Not available
HEADLAMPS	Dual halogen composite with flash-to-pass feature, automatic exterior lamp control and daytime running lamps. Daytime running lamps are low beam lamps and operate at a reduced intensity (to delete automatic lamp control see available options page). Drilling headlamps is an alteration for which General Motors is not responsible for nor the effects of the alterations.
HORNS	Dual note
KEYS	Two-sided, random code, for ignition, driver door and glove box. Six additional keys are available (maximum 8 keys can be programmed per vehicle). see available options page. Fleet keyed-alike is available; see available options page.
KEYLESS ENTRY REMOTES	Includes two extended-range transmitters with non-functional panic button; stealth mode feature includes exterior lamps and horn disable as default setting. Remote feedback is programmable via radio settings if light and or horn lock/unlock notification is desired. Running lamps will remain illuminated when optional (BTV) remote start is activated. Additional transmitters are available; see available options page.
LUGGAGE RACK	Not available
MIRRORS	Outside heated power-adjustable, manual-folding, body color with driver side spotter mirror
REAR LIFTGATE	Manual open/close with liftgate/liftglass latch exterior release switch or release via remote fob
REAR PARK ASSIST	Sensors on rear bumper to assist with parking and avoiding objects while in reverse. (see illustration section for description)
REAR VISION CAMERA	Audible warning with rear camera view radio screen display (see illustration section for description)
UNDER HOOD LAMP	Not available
WINDSHIELD	Solar absorbing shaded upper with acoustic laminated glass
WINDSHIELD WIPERS	Intermittent, with rain sensing
STANDARD 5W4 ELECTRICAL FEATURES	
AUXILIARY POWER, FRONT	170-amp ignition and main power supply wiring at lower center of instrument panel; 120-amp ignition controlled relay power and 50- amp battery power (see wiring diagram section for description)
AUXILIARY POWER, REAR	100-amp cargo area (auxiliary battery powered) (see illustrations section for description)
LOCK-OUT PROTECTION	Factory default condition on 9C1 allows all doors to be locked while a key is in the ignition by use of power door lock button. Auto lock-out can easily be enabled in the Radio VEHICLE SETTINGS menu to prevent power door locks from locking the driver's door if the keys are left in the ignition (see standard equipment illustrations section).
POWER OUTLETS	4 auxiliary, 12-volt outlets including one on the instrument panel, one in the center, fold-down seat storage, and two in the cargo area. Battery power is present at all times. Also has a 3-prong, 110-volt outlet located in the lower center stack. One 110 volt, 60 Hertz power outlet rated 150 watts (1.36 amps at 110v), located in the lower instrument panel center stack. Overload power before automatic shut off is 275 watts for 10 seconds or 418 watts for 1 second.
WIRING DIAGRAMS	See Wiring Section for description (see wiring diagram section for description); also see Tahoe Police Package owner's manual supplement (located in glove box folder with standard owner's manual)

2016 TAHOE 4x4 SPECIAL SERVICE

NOTE: The four-wheel drive Tahoe Special Service (5W4) offers you support in general utility for off-road and non-pursuit operations. GM restricts the sale of police vehicles and they are not to be sold to retail customers. Model CK15706 (four-wheel drive) with equipment group 1FL is required when ordering 5W4 Special Service package. Two-wheel drive model is not available.

STANDARD 5W4 INTERIOR FEATURES

AIR CONDITIONING	Dual-zone automatic, includes front and rear air conditioning with electronic controls
ASSIST HANDLES	Front passenger and second row outboard; front passenger assist handle is deleted when passenger side spotlamp is ordered
BACK-UP CAMERA	Displayed in radio screen
BACK-UP SENSORS	Rear Park Assist with audible warning
BLUETOOTH	Bluetooth ¹ cell phone connectivity Displayed on radio screen (see standard equipment illustrations section) (deleted when UE0 OnStar delete is ordered) Bluetooth microphone is same location as OnStar. It is located on the headliner in front of driver's sun visor. Bluetooth phone conversations are broadcast over the 4 front speakers only (left front door/right front door/left dash/right dash pad). Extra loud warning chimes broadcast through left front door speaker and left front dash speaker only.
COMPASS	Displayed in Driver Information Center See standard equipment illustrations section (Compass is deleted when UE0 OnStar Delete is ordered)
CONNECTIVITY	OnStar with 4G LTE provides a built-in Wi-Fi ² hotspot to connect to the internet at 4G LTE speeds. Included and only available with (UE1) OnStar. Visit www.onstar.com for vehicle availability, details and system limitations. Services and connectivity may vary by model and conditions. 4G LTE service available in select markets. 4G LTE performance based on industry averages and vehicle systems design. Some services require data plan.
CONSOLE, OVERHEAD	Includes conversation mirror and sunglass holder with map lights and passenger airbag indicator
CRUISE CONTROL	Electronic with set and resume speed
FLOOR COVERING	Black rubberized vinyl floor and load floor behind second row seats, see illustration section for description (carpeting and carpeted floor mats are available, see available options page)
GLASS	Deep-tinted, all windows (except for windshield, and driver/front-passenger side glass which are light-tinted). Front doors have a 24.6% UV transmission Rear door and cargo glass is 12% +/- 3% transparency and front glass has 70% minimum. Non-tinted, solar absorbing glass available (see available options page).
GLOVE BOX	Locking door without courtesy light (uses ignition key)
LIGHTING	Interior LED with courtesy lights, door handle or remote entry activated, illuminated entry and map lights
MIRROR	Inside, rearview, manual day/night
NAVIGATION	Available only with active OnStar ³ account that includes Turn-by-Turn directions plan; directions are displayed as text on radio. Does not include map view navigation screen.
ONSTAR⁴	OnStar Directions and Connections plan for 6 months, including Automatic Crash Response, Stolen Vehicle Assistance, Roadside Assistance and Turn-by-Turn Navigation. Visit www.onstar.com for vehicle availability, details and system limitations. Services may vary by model and conditions NOTE: Activation of an OnStar account requires the request of customer to initiate once vehicle is received
OUTSIDE TEMPERATURE	Displays in top right corner of radio screen (see standard equipment illustrations section)
RADIO	AM/FM stereo with CD player and auxiliary input jack, includes 4.2 inch radio screen, USB-ports, MP3 player and 6-speaker system (see standard equipment illustrations section)
RESTRAINT SYSTEM	Three point safety belts, driver and front passenger with pretensioners, dual stage driver and front passenger frontal airbags, driver and passenger knee bolsters, front passenger sensing system with frontal airbag ON/OFF indicator, rollover sensor, dual head curtain airbags for front and second row outboard occupants ⁵ and front seat-back mounted thorax-pelvic airbags; head curtain airbag extends to cargo area
SEATS, FRONT	CLOTH 40/20/40 individual seats, 3 passengers with 10-way power driver seat adjuster (fore/aft, up/down, tilt, recline, and lumbar), and 6-way power passenger seat adjuster. Adjustable outboard head restraints and storage pockets. Center seat section can be deleted (9U3) for 15" of open floor space (see front seats and interior trim illustration page for description).
SEAT, REAR	CLOTH split-folding 60/40 bench seats includes folding center armrest with cup holders, outboard seating position headrests and reclining rear seat back. (Vinyl 2nd row seat option 5T5) 3rd row seats not available (see front seats and interior trim illustration page for description)
SPEEDOMETER/CLUSTER	Digital Speedometer and 140 mph analog speedometer, 1 mph increments and digital trip odometer with gauges for engine oil pressure, fuel, battery volts, coolant temperature and tachometer. Driver Information Center displays engine hours, warnings, and backup sensor proximity status while in reverse (see message listing for additional features).
STEERING WHEEL	Tilt-wheel with cruise control and column mounted gear shift lever. (Vehicles equipped with safety alert package will also have wheel mounted sensitivity on/off controls)
SURVEILLANCE FEATURE	Body Control Module calibration is available to disable all automatic interior and exterior lighting. Feature requires connection to BCM by customer. Feature operates with or without SE0 9G8, delete Daytime Running Lamps and Automatic Headlamps. (see illustration section for description)
THEFT DETERRENT SYSTEM	Vehicle PASS-Key [®] III+ and Content Theft (unauthorized entry, or entry without remote unlock will sound horn and flash lamps). Option UTQ must be ordered for content theft disable
VISORS	Padded with cloth trim, extends on rod; driver and front passenger illuminated vanity mirrors
WARNING TONES	Headlamp on, key-in-Ignition, driver and right-front passenger safety belt unfasten, backup sensor with warning tone and turn signal on
WINDOW OPERATION	Power with driver express up/down and lockout features

1. The Bluetooth word mark is a registered trademark owned by Bluetooth SIG, Inc. and any use of such mark by GM is under license. Go to gm.com/bluetooth to find out which Bluetooth phones are compatible with the vehicle.

2. Visit onstar.com for coverage map, details and system limitations. OnStar acts as a link to existing emergency service providers. Services vary with model and conditions. Available on select iPhone, [®]Android[™] and BlackBerry[®] devices. Services vary by phone, vehicle and conditions. Requires active OnStar subscription. Not available in certain areas. Visit onstar.com for coverage map, details and system limitations. Ability to locate stolen vehicles and remote door unlock success varies with conditions.

3. Always use safety belts and the correct child restraint for your child's age and size, even in vehicles equipped with airbags. Even in vehicles equipped with Passenger Sensing System, children are safer when properly secured in a rear seat in an appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal airbag. See your vehicle Owner Manual and child safety seat instructions for more information.

4. Devices must be WPA2 compliant with active OnStar service and data plan. Wi-Fi devices manufactured prior to 2006 may not be compatible. Please consult your device manufacturer for information regarding the WPA2 security protocol and Wi-Fi device compatibility. Visit onstar.com for vehicle availability, details and system limitations. Services and connectivity may vary by model and conditions. 4G LTE service available in select markets. Some services require a data plan. Vehicle must be started or in accessory mode.

OPTIONAL EQUIPMENT & FEATURES

EXTERIOR

- 9G8 DELETE DAYTIME RUNNING LAMPS AND AUTOMATIC HEADLAMPS** - Exterior lamps are operated manually (see Interior/Exterior Lamps Control descriptive)
- 5T4 EXTERIOR BODY COLOR PARTS** - SEO 5T4 Exterior body colored parts. Victory Red special painted exterior body parts in lieu of glossy Black color normally installed with special painted bodies, Victory Red painted parts will consist of front fascia, rear bumper fascia, rear liftgate handle, and door handles. Mirrors, rear D-pillar appliqué and liftgate spoiler will remain Black. Requires SEO (TGK) special paint solid, special paint color Victory Red WA-9260 and (V76) recovery hooks.
- 9V7 EXTERIOR BODY COLOR PARTS** - Dark Blue Metallic, special paint WA-722J applied to front fascia, rear bumper fascia, rear liftgate handle and liftgate appliqué above license plate. Door Handles, Mirrors, rear D-pillar appliqué and liftgate spoiler will remain Black. Includes opening in front fascia without recovery hooks (requires TGK special paint solid) Recovery hooks (V76) optional.
- 9V2 EXTERIOR BODY COLORED PARTS** - Blue WA-5665 applied to front and rear fascia. All other non-metal body parts will remain the same as (TGK) special paint solid. Includes opening in front fascia without recovery hooks (requires TGK special paint solid) Recovery hooks (V76) optional.
- 8J7 FLASHER SYSTEM HEADLAMPS AND TAIL LAMPS** - DRL compatible, headlamp flasher module with control wire to permit separate front and rear lamp flashing
- AKP GLASS - NON-TINTED GLASS** - Solar absorbing (replaces deep-tinted glass on rear doors and cargo area)
- UT7 GROUND STUDS** - Two located in rear compartment near bottom of liftgate opening
- VK3 LICENSE PLATE** - Front mounting package (included on orders with ship-to states that require front license plate) See illustrations section for description
- VQK MOLDED SPLASH GUARDS** - Black
- RWIK MOLDINGS PAINTED BODY SIDE** - Painted body-side moldings are available with (G7U) Sable Metallic, (GAZ) Summit White, (GBA) Black and (GWT) Champagne Silver
- 7X6 SPOTLAMP** - Left hand, separately fused, Not available with (7X7) left and right-hand spotlamps (see illustrations section for description)
- 7X7 SPOTLAMPS** - Left and right hand, separately fused (see illustrations section for description)
- SGN TRAILER HITCH INSERT** - Black rubber square with a logo that closes out the receiver see illustrations section for description (Dealer installed)

ELECTRICAL

- WX7 WIRING** - For customer connection to front door and windshield pillar speakers. Front speakers are not connected to the vehicle radio; radio audio signals are routed to the rear speakers
- 8J3 WIRING** - For grille lamps and siren speaker
- 8J4 WIRING** - For horn/siren circuit, in-line connection for customer furnished switch

CHASSIS

- R9Y FLEET FREE MAINTENANCE CREDIT** - This option code provides a credit in lieu of the free oil changes, tire rotations and inspections (2 maximum), during the first 24 months and 24,000 miles period for this ordered vehicle. The invoice will detail the applicable credit. The Customer will be responsible for all oil changes, tire rotations and inspections cost for this vehicle. NOTE: Dealer is unable to credit customer on vehicles not originally ordered with (R9Y) option.
- K05 HEATER** - Engine block
- 5W4 IDENTIFIER** - Special Service
- 9G3 SUSPENSION PACKAGE** - Off-Road, includes (K47) High capacity air cleaner and (NZZ) Skid Plate Package. Requires (RC3) P265/70R17 all-terrain, blackwall tires or (R18) 18" Goodyear Wrangler DuraTrac 265/65R18 blackwall tires with aggressive tire tread. Not available with (NHT) Max Trailering Package.
- GUG REAR AXLE** - 3.42, Requires with (NHT) Maximum Trailering Package
- R117 TRAILERING PACKAGE MAX** - Includes (GUG) 3.42 rear axle, (JL1) trailer brake controller and (Z85) suspension package (Requires PZX aluminum wheels and RKX 18 in. all-season tires) increases standard maximum trailer weight from 6400 lbs to 8400 lbs
- R18 TIRES** - 265/65R18 blackwall Goodyear Wrangler DuraTrac. Aggressive tread may result in a higher level of noise while driving. Routine tire rotations are strongly recommended. Requires SEO (9G3) Off-Road Suspension Package.
- RC3 TIRES** - P265/70R17 all-terrain, blackwall
- RKX TIRES** - P265/65R18 all-season blackwall. Requires option (PZX) 18 inch aluminum wheels
- 4JQ TIRE** - Spare P265/70R17 all-terrain, blackwall (Requires RC3 all-terrain tires)
- PZX WHEELS** - 18 in. x 8.5 in. (45.7 cm x 21.6 cm) aluminum with high-polished finish. Requires (R18) or (RKX) P265/65R18 all-season, blackwall tires. See illustrations section for description

Note: Factory installation of spotlamps are recommended. Special tooling is used to locate and drill the spotlamp shaft hole in the pillars. (Interior trim covers provided with factory installed lamps are not available as service parts). Field installation of spotlamps must not interfere with proper deployment of the roof rail airbag in the event of a crash.

**2016 Tahoe SSV (add – on lighting options)
CODE3 Lighting systems as highlighted below**

Side Mirror (Pair): XT4 XT4OMMNT-TH15
MR6 MR6OMMNT-TH15

Grille (Pair): XT4 GMBTH15

C3100 Speaker: - Single C3100 C3100TH15

Rear Quarter Window: XT302 RSWMNT-TH15

Rear Window: XT4 CITTH15-XX
Citadel kit with (6) XT4 LED (CT)& bracket (BYO)

License Plate Bracket: XT3 LPBKT-TH15