

Detailed Specifications

Three (3) 2017 Ford F-250 SRW, 4X4, Super Cab, Cab & Chassis Standard XL Trim. 9900 lbs. GVWR, 158" WB and 56.2" CA
Engine: 6.2L 2 Valve Flex Fuel V8 Gas Engine
Transmission: Torqueshift, 6 Speed Automatic with Overdrive
Rear Axle: 3.73 Non-Limited-Slip Axle Ratio
Brakes: Power 4-Wheel Disc, 4 Wheel Anti Lock Brake System
Alternator: Extra Heavy Duty
Battery: 12 volt; 650-CCA/72-amp-hr
Shocks: Manufactures Standard Heavy Duty– Front and Rear
Tires: LT245/75R17E BSW A/S (4)
Wheels: 17" Argent Steel (4)
Fuel Capacity: 35 Gallons
Seats & Seat Trim: HD Vinyl 40/20/40 Split Bench Seats
Radio: AM / FM Stereo w/Clock & 2-speakers
Mirrors: Manually Trailer Tow with Power Heated Glass
Color: Exterior - Oxford White Interior - Heavy Duty Vinyl, Steel
Equipment Group/Options: 66D Box Delete Power Equipment Group Exterior Back-Up Alarm 6" Angular Black Molded in Color Running Boards 4x4 Electronic-Shift-On-the-Fly Up fitter Switches (4) Cruise Control Air Conditioning – Manufactures Standard Heavy Duty Black Vinyl Floor Covering Four Sets of Keys

Detailed specifications

Description: Reading Aluminum Classic II, Standard Spacemaker Service Body With Aluminum Sliding Top
Body Construction: Aluminum
Body Model: US98-SWs
Understructure: Heavy-gauge aluminum crossmembers and longitudinal rails
Hardware: Stainless steel rotary locks with paddle handles
Floor: 1/8" aluminum diamond plate floor
Color: Oxford white Z1
Lighting: LED marker and clearance lamps flush mounted
Compartment Layout: Driver's Side: "A" compartment layout Passenger's Side: "B" compartment layout
Compartment Shelving: P/S & D/S front verticals: Three (3) adjustable shelves with movable dividers. Horizontals: One (1) shelf with movable dividers. D/S rear vertical: Three (3) adjustable shelves with movable dividers. P/S rear vertical: Open, no shelves
Rear Bumper: Pooched Bumper
Compartment Lighting System: All compartments and cargo area to be equipped with manufactures standard LED lights. All lights to be wired to supplied upfitter switches in cab. Wiring as follows: Cargo light – One switch and labeled L/S and R/S compartment lights – One switch and labeled Beacon Light – One switch and labeled
Additional Options: Master locking system Aluminum Treadplates mounted on front of body panels and on top of tailgate Aluminum Sliding Top, model ST-98
Safety Light: Supply and Install: One (1) RTM-101LP-F150-15 ACARI mounting plate with Whelen ROTA-BEAM super – LED R416AF beacon light. Light to be wired to upfitter switch in cab and labeled
Grab Handles: Two (2) mounted vertically on rear of body for easy access
Back Up Camera: Supply and install Rosco backup camera system, part number STSK4533. Camera shall activate when vehicle is placed into reverse.