

## **Hurley Fire Department # 1**

### **2017 TAHOE 4x4 SPECIAL SERVICE**

#### **GENERAL**

Model CK15706

Drive 4-wheel

Exterior Color – Summit White - GAZ

Interior – Black / Cloth

**AIR CONDITIONING** Dual-zone automatic, includes front and rear air conditioning with electronic controls

**BACK-UP CAMERA** Displayed in radio screen

**BACK-UP SENSORS** Rear Park Assist with audible warning

**BLUETOOTH** Bluetooth<sup>®</sup> cell phone connectivity Displayed on radio screen (see standard equipment illustrations section) (deleted when UE0 OnStar delete is ordered) Bluetooth microphone is same location as OnStar. It is located on the headliner in front of driver's sun visor. Bluetooth phone conversations are broadcast over the 4 front speakers only (left front door/right front door/left dash/right dash pad).

**COMPASS** Displayed in Driver Information Center See standard equipment illustrations section (Compass is deleted when UE0 OnStar Delete is ordered)

**CONNECTIVITY** OnStar with 4G LTE provides a built-in Wi-Fi<sup>®</sup> hotspot to connect to the internet at 4G LTE speeds. Included and only available with (UE1) OnStar. Visit [www.onstar.com](http://www.onstar.com) for vehicle availability, details and system limitations. Services and connectivity may vary by model and conditions. 4G LTE service available in select markets. 4G LTE performance based on industry averages and vehicle systems design. Some services require data plan.

**CONSOLE, OVERHEAD** Includes conversation mirror and sunglasses holder with map lights and passenger airbag indicator

**CRUISE CONTROL** Electronic with set and resume speed

**FLOOR COVERING** Black rubberized vinyl floor and load floor behind second row seats, see illustration section for description (carpeting and carpeted floor mats are available, see available options page)

**GLASS** Deep-tinted, all windows (except for windshield, and driver/front-passenger side glass which are light-tinted). Front doors have a 24.6% UV transmission Rear door and cargo glass is 12% +/- 3% transparency and front glass has 70% minimum. Non-tinted, solar absorbing glass available (see available options page).

**GLOVE BOX** Locking door without courtesy light (uses ignition key)

**LIGHTING** Interior LED with courtesy lights, door handle or remote entry activated, illuminated entry and map lights

**MIRROR** Inside, rearview, manual day/night

**NAVIGATION** Available only with active OnStar<sup>®</sup> account that includes Turn-by-Turn directions plan; directions are displayed as text on radio. Does not include map view navigation screen.

**ONSTAR<sup>®</sup>** OnStar Guidance Plan for 6 months, including Automatic Crash Response, Stolen Vehicle Assistance, Roadside Assistance and Turn-by-Turn Navigation. Visit [www.onstar.com](http://www.onstar.com) for vehicle availability, details and system limitations. Services may vary by model and conditions **NOTE: Activation of an OnStar account requires the request of customer to initiate once vehicle is received**

**OUTSIDE TEMPERATURE** Displays in top right corner of radio screen (see standard equipment illustrations section)

**RADIO** AM/FM stereo with CD player and auxiliary input jack, includes 4.2 inch radio screen, USB-ports, MP3 player and 6-speaker system. Radio Data Systems (RDS) capable. (see standard equipment illustrations section)

**RESTRAINT SYSTEM** Three point safety belts, driver and front passenger with pretensioners, dual stage driver and front passenger frontal airbags, driver and passenger knee bolsters, front passenger sensing system with frontal airbag ON/OFF indicator, rollover sensor, dual head curtain airbags for front and second row outboard occupants<sup>3</sup> and front seat-back mounted thorax-pelvic airbags; head curtain airbag extends to cargo area

**SEATS, See options.**

**SEAT, REAR CLOTH** split-folding 60/40 bench seats includes folding center armrest with cup holders, outboard seating position headrests and reclining rear seat back. (Vinyl 2nd row seat option 5T5) 3rd row seats not available (see front seats and interior trim illustration page for description)

**SPEEDOMETER/CLUSTER** Digital Speedometer and 140 mph analog speedometer, 1 mph increments and digital trip odometer with gauges for engine oil pressure, fuel, battery volts, coolant temperature and tachometer. Driver Information Center displays engine hours, warnings, and backup sensor proximity status while in reverse (see message listing for additional features).

**STEERING WHEEL** Tilt-wheel with cruise control and column mounted gear shift lever.

**VISORS** Padded with cloth trim, extends on rod; driver and front passenger illuminated vanity mirrors

**WARNING TONES** Headlamp on, key-in-ignition, driver and right-front passenger safety belt unfasten, backup sensor with warning tone and turn signal on

**WINDOW OPERATION** Power with driver express up/down and lockout features

**ASSIST STEPS** Black, mounted between front and rear wheels

**DEFOGGER** Electric, rear window

**DOOR HANDLES** Body color

**DOOR LOCKS** Power, programmable with lockout protection and automatic locking/unlocking. Door locks can be programmed via radio settings menu (see standard equipment illustrations section). Lock cylinder not available on passenger front door or rear liftgate. Child safety door and window locks individually controlled electronically by driver door mounted switches. Includes 2 remote transmitters.

**FASCIA, FRONT** Body color with police specific lower extension for increased brake cooling and ground clearance

**FASCIA, REAR** Body color with step pad

**FOG LAMPS** Not available

**HEADLAMPS** Dual halogen composite with flash-to-pass feature, automatic exterior lamp control and daytime running lamps. Daytime running lamps are low beam lamps and operate at a reduced intensity (to delete automatic lamp control see available options page). Altering headlamp assembly is not recommended, General Motors is not responsible for the effects of any modifications.

**HORNS** Dual note

**KEYS** Two-sided, random code, for ignition, driver door and glove box. Six additional keys are available (maximum 8 keys can be programmed per vehicle). see available options page. Fleet keyed-alike is available; see available options page.

**KEYLESS ENTRY REMOTES** Includes two extended-range transmitters with non-functional panic button; stealth mode feature includes exterior lamps and horn disable as default setting. Remote feedback is programmable via radio settings if light and or horn lock/unlock notification is desired. Running lamps will remain illuminated when optional (BTV) remote start is activated. Additional transmitters are available; see available options page.

**MIRRORS** Outside heated power-adjustable, manual-folding, body color with driver side spotter mirror

**RADIO ANTENNA** Located in rear quarter glass

**REAR LIFTGATE** Manual open/close with liftgate/liftglass latch exterior release switch or release via remote fob

**REAR PARK ASSIST** Sensors on rear bumper to assist with parking and avoiding objects while in reverse. (see illustration section for description)

**REAR VISION CAMERA** Audible warning with rear camera view radio screen display (see illustration section for description)

**UNDER HOOD LAMP** Not available

**WINDSHIELD** Solar absorbing shaded upper with acoustic laminated glass

**WINDSHIELD WIPERS** Intermittent, with rain sensing

## **STANDARD 5W4 ELECTRICAL FEATURES**

**AUXILIARY POWER**, 170-amp ignition and main power supply wiring at lower center of instrument panel: 120-amp ignition controlled relay power and **FRONT** 50- amp battery power (see wiring diagram section for description)

**AUXILIARY POWER, REAR** 100-amp cargo area (auxiliary battery powered) (see illustrations section for description)

**LOCK-OUT PROTECTION** Factory default condition on 9C1 allows all doors to be locked while a key is in the ignition by use of power door lock button. Auto lock-out can easily be enabled in the Radio VEHICLE SETTINGS menu to prevent power door locks from locking the driver's door if the keys are left in the ignition (see standard equipment illustrations section).

**POWER OUTLETS** 110-volt (3 prong outlet) located in the lower center stack. 110 volt, 60 Hertz power outlet is rated 150 watts (1.36 amps at 110v). Overload power before automatic shut off is 275 watts for 10 seconds or 418 watts for 1 second. Also includes four auxiliary 12-volt outlets including one on the instrument panel, one in the center fold-down seat storage, and two in the cargo area. Outlet power is configurable to be Battery Powered at all times or Ignition Controlled Power. See the Standard Equipment Section for description of selecting Outlet power configuration.

**WIRING DIAGRAMS** See Wiring Section for description; also see Tahoe Police Package owner's manual supplement (located in glove box folder with standard owner's manual)

**AIR CLEANER** High-capacity

**ALTERNATOR** 170-amp high output with idle boost based on battery energy level (see specifications page for description)

**AXLE -see towing package**

**BATTERIES** Primary 720 CCA, 80 amp-hour rating with battery rundown protection (may be configured to protect customer installed equipment). Isolated, Auxiliary 730 CCA, 70 amp-hour battery without battery run-down protection for customer installed equipment. (see specifications page)

**COOLING** Heavy-duty high-capacity radiator, electric fans and extended life coolant; coolant hoses are EPDM (ethylene-propylene-diene monomer) rubber; silicone hoses are not required (coolant is DEX-COOL good for 5 years/150,000 miles, protects from -34° F to +265° F and against rust and corrosion)

**ENGINE** 5.3L EcoTec3 V8 with direct injection, variable valve timing (VVT), Active Fuel Management (AFM), aluminum block, and FlexFuel capability (gasoline or E85 ethanol); includes air conditioning wide open throttle cut off (see specifications page)

**EXHAUST** Aluminized stainless-steel muffler and tailpipe

**FRAME** Full perimeter, modular with hydroformed rails (includes ground straps)

**FUEL TANK CAPACITY** 26 gallon (98 liters)

**HILL START ASSIST** This feature is designed to prevent the vehicle from rolling, either forward or rearward, during vehicle drive off.

**OIL COOLERS** Engine oil, oil-to-coolant heat exchanger in passenger side of coolant radiator. Transmission oil, oil-to-coolant heat exchanger in driver side of coolant radiator with auxiliary transmission air-to-oil cooler in upper portion of the AC condenser (see illustration section for description).

**PROP SHAFT** 4 inch diameter aluminum

**RADIO SUPPRESSION** Grounding straps, at five locations (see illustration section for location)

**REAR DIFFERENTIAL** Heavy-duty locking

**SPARK PLUGS** Extended life - iridium tip

**STABILITRAK** An advanced computer controlled stability enhancement system assists the driver with directional control of the vehicle in difficult driving conditions. (See illustration section for Stabilitrak button location and Stabilitak page for description)

**STEERING** Electric power-assisted rack and pinion (see illustrations section for description)

**SUSPENSION, FRONT** Coil-over-shock with stabilizer bar

**SUSPENSION, REAR** Multi-link with coil springs with stabilizer bar

**TIRE PRESSURE MONITOR** Check tire pressure will display in driver message center; also displays individual tire pressure (see illustrations section for description)

**TIRE, SPARE** Full-size spare, lockable with outside winch-type carrier mounted under frame at rear (TPM sensor not included).

**TRAILERING EQUIPMENT** SAE Class II hitch. Trailer may weigh up to 6,300 pounds with proper hitch selection. 8,400 lb Max Trailering Package (NHT) optional. See the Owners Manual for additional information.

**TRANSMISSION** Enhanced calibration 6-speed automatic with overdrive and tow/haul mode. Electronically-controlled transmission provides protection against over-revving the engine in low gear and a mechanical low gear blockout is not required; if a driver manually selects low gear and fails to manually upshift to high gear, the powertrain control module automatically protects the drivetrain.

**TRANSFER CASE** Autotrac, 2-speed electronic with rotary control, includes neutral position for dinghy towing (2HI, 4AUTO, 4HI, 4LO, and Neutral setting) See owners manual procedure for shifting into N (Neutral) and shifting out of N (Neutral).

### ***Routing Grommet***

**UNDER BODY SHIELD, FRONT** Two piece heavy-duty aluminum front underbody shield starting behind front bumper and running to 2nd cross-member protecting front underbody and oil pan (see illustrations section for description)

**NE1 CT/DE/ME/MD/MA/NJ/NY/OR/PA/RI/VT/WA EMISSIONS.** Connecticut, Delaware, Maine, Maryland, Massachusetts, New Jersey, New York, Oregon, Pennsylvania, Rhode Island, Vermont and Washington state requirements

## **Options**

### **INTERIOR**

**U77 GROUND STUDS** - Two interior mounted left and right side M10 studs in cargo area. Driver side includes 5 feet of 8 gauge ground wire.

**6C7 LAMP, AUXILIARY DOME** - Red and white auxiliary dome lamp is located on the headliner between front row seats (red is LED, white is INCANDESCENT). (wired independently from standard dome lamp)

**JF4 PEDALS** - Power-adjustable for accelerator and brake

**V76 RECOVERY HOOKS** - Two black front frame-mounted, recommended if front push bumper is to be installed (required on all models sold to Alaska, Guam, Hawaii, Puerto Rico and Virgin Islands)

**BTV REMOTE VEHICLE STARTER SYSTEM** - Includes remote keyless entry

**9U3 SEAT DELETE FRONT CENTER** - Front center seat (20% seat) delete, Power driver and passenger bucket seats in base cloth trim. Derived from RPO (AZ3) 40-20-40 split bench seat with the 20% section removed. Does not include a floor console. All exposed floor area will remain untrimmed. Not available with (A95) Bucket Seats. Requires (H0U) Jet Black trim.

**5T5 SEAT** - Front cloth with vinyl rear seat (see front seats and interior trim illustration page for description)

**6J7 FLASHER SYSTEM HEADLAMPS AND TAIL LAMPS** - DRL compatible, headlamp flasher module with control wire to permit separate front and rear lamp flashing

**VK3 LICENSE PLATE** - Front mounting package (included on orders with ship-to states that require front license plate) See illustrations section for description

**VQK MOLDED SPLASH GUARDS** – Color of body

**B86 BODY SIDE LOWER DOOR MOLDINGS**- Body color (Not available with B85 or 01U special paints)

**7X6 SPOTLAMP** - Left hand, separately fused, Not available with (7X7) left and right-hand spotlamps (see illustrations section for description)

## **ELECTRICAL**

**6J3 WIRING** - For grille lamps and siren speaker

**6J4 WIRING** - For horn/siren circuit, in-line connection for customer furnished switch

**UT7 GROUND STUDS** - Two interior mounted left and right side M10 studs in cargo area. Driver side includes 5 feet of 8 gauge ground wire.

## **CHASSIS**

**K05 HEATER** - Engine block

**9G3 SUSPENSION PACKAGE** - Off-Road, includes (K47) High capacity air cleaner and (NZZ) Skid Plate Package. Requires (RC3) P265/70R17 all-terrain, blackwall tires or (R18) 18" Goodyear Wrangler DuraTrac 265/65R18 blackwall tires with aggressive tire tread. Not available with (NHT) Max Trailering Package.

**GU6 REAR AXLE** - 3.42, Requires (NHT) Maximum Trailering Package

**NHT TRAILERING PACKAGE, MAX** - Includes (GU6) 3.42 rear axle, (JL1) trailer brake controller, and (Z85) suspension package (Requires PZX aluminum wheels and RKX 18 in. all-season tires) Increases standard maximum trailer weight from 6400 lbs to 8400 lbs.

**R18 TIRES** - 265/65R18 blackwall Goodyear Wrangler DuraTrac. Aggressive tread may result in a higher level of noise while driving. Routine tire rotations are strongly recommended. Requires SEO (9G3) Off-Road Suspension Package.

**PZX WHEELS** - 18 in. x 8.5 in. (45.7 cm x 21.6 cm) aluminum with high-polished finish. Requires (R18) or (RKX) P265/65R18 all-season, blackwall tires. (See illustrations section for description)

SEO (9G3) Off-Road Suspension Package.