



Kenworth of Buffalo NY Inc K855
100 Commerce Drive

ERIE COUNTY WATER AUTHORITY

Lackawanna, New York United States 14218

Phone: (716) 852-2800
Fax: (716) 852-0143
Email:

Phone:
Fax:
Contact Email:
Prepared for:

Dump

Vehicle Summary

Unit		Chassis	
Model:	T300 Series Conventional.	Fr Axle Load (lbs):	18000
Type:	FULL TRUCK	Rr Axle Load (lbs)	27120
Description:	New Pres101953	G.C.W. (lbs):	45120
Application		Road Conditions:	
Intended Serv.:	Construction. Vehicles used in the construction	Class A (Highway)	85
Commodity:	Gravel/crushed rock/sand	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	05
Type:	End dump	Class D (Off-Road)	00
Length (ft):	12.0	Maximum Grade:	6
Height (ft):	12.0	Wheelbase (in):	188 172"
Max Laden Weight (lbs):	4000	Overhang (in):	71
Trailer		Fr Axle to BOC (in):	68
No. of Trailer Axles:	0	Cab to Axle (in):	120 104"
Type:		Cab to EOF (in):	191
Length (ft):	0.0	Overall Comb. Length (in):	300
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	U.S. Domestic Registry, 50-State	
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 3/17/2016 1:53:31 PM
Effective Date: Jan 1, 2016
Prepared by: Administrator

Incomplete

Model Number: T300 Series Conventional.
Quote/DTPO/CO: Q25385224
Version Number: 37.10



Kenworth of Buffalo NY Inc K855
100 Commerce Drive

ERIE COUNTY WATER AUTHORITY

Lackawanna, New York United States 14218

Phone: (716) 852-2800

Fax: (716) 852-0143

Email:

Phone:

Fax:

Contact Email:

Prepared for:

Model	Description	Weight
	T300 Series Conventional. Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floormat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,764
	T370 Class 7: medium-duty Conventional.	0
	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
	Medium-duty 18k/20k Heavy Front Axle.	0
	Gravel/crushed rock/sand	0
	Construction. Vehicles used in the construction industry, other than those listed above. Use typically involves operating on the jobsite, to pick up or deliver construction materials, or to position the vehicle for its intended use at the construction site. Includes such activities as delivery of precast concrete, concrete pumers, flatbeds or roll-offs for delivery of construction materials or equipment, etc. Typically includes some operation off of paved roads. Road usage: any combination, which includes some Class C.	0
	End dump	0
	U.S. Domestic Registry, 50-State	0

Engine & Equipment

PACCAR PX-9 300 2013 300@2000 285@2200 860@1300.	555
Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing.	
N09200 N205 120..Standard Maximum Speed Limit [LSL]	
N09220 N207 0....Expiration Distance	
N09240 P09 120...Hard Maximum Speed Limit	
N09260 P14 69...Maximum Accelerator Pedal Vehicle Speed	
N09280 P16 0....Accelerator Lower Droop	
N09300 P19 69...Maximum Cruise Speed	
N09320 C143 0....Cruise Control Lower Droop	
N09360 N203 252..Reserve Speed Function Reset Distance	
N09380 N202 0....Maximum Cycle Distance	

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
N09400 N206 10...Maximum Active Distance	
N09420 N201 0....Reserve Speed Limit Offset	
N09440 P11 No...Engine Protection Shutdown	
N09460 P06 No...Gear Down Protection	
N09480 P26 1400.Max PTO Speed	
N09500 P02 No...Cruise Control Auto Resume	
N09520 P04 No...Auto Engine Brake in Cruise	
N09540 N209 0....Expiration Distance	
N09560 P520 Yes..Enable Idle Shutdown Park Brake Set	
N09580 P32 5....Timer Setting	
N09600 P233 Yes..Enable Impending Shutdown Warning	
N09620 P234 60...Timer For Impending Shutdown Warning	
N09640 P516 35...Engine Load Threshold	
N09680 P33 No...Idle Shutdown Manual Override	
N09720 P230 Yes..Enable Hot Ambient Automatic Override	
N09740 P46 40...Low Ambient Temperature Threshold	
N09760 P56 60...Intermediate Ambient Temperature Threshold	
N09780 P47 80...High Ambient Temperature Threshold	
Prospector Version 37.1	0
Replaces 37.0	
Effective VSL Setting NA	0
Engine Idle Shutdown Timer Enabled	0
Eff EIST NA Expiration Miles	0
Use only with MX and Cummins engines	
Air compressor: Cummins 18.7 CFM, Cummins, PACCAR PX engines.	0
Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
Pre-filter hood mounted for air cleaner & HVAC.	13
Fan Hub: Horton 2-Speed for ISL9, ISL-G, PX-8 or PX-9	0
Cooling module: 1000 square inches	0
T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	
RH under cab SCR for PX-8, PX-9 w/single vertical RH SOC tailpipe.	101
Tailpipe: 5 in. single 36 in. 45 degree curved.	1
For use with any Exhaust other than SCR Independent.	
Fleetguard Filter/Water separator FS1003 12V Heat w/WIF (water in fuel) sensor.	0
Block heater, PACCAR 1750 watt 120V for PX-6 and PX-7, 1000 watt for PX-8 and PX-9 or ISL9 engines .	2
Alternator: PACCAR 160 amp, brush type	0
Batteries: 3 PACCAR GP31 threaded post (700) 2100 CCA dual purpose.	57
12-VOLT LIGHT SYSTEM W/CIRCUIT PROTECTION	

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
Multi-function engine connector for body builder interface for Cummins.	0
Transmission & Clutch	
Transmission: Allison 3500RDS 6-speed w/PTO drive gear. 5th Gen Controls. Limited to 860 lb.-ft. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	291
Driveline: 2 SPL170XL 1 centerbearing requires 3500057 interaxle driveline.	70
One heavy-duty centerbearing crossmember. This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	11
Torque converter included w/Allison Transmission.	0
Delete Allison FuelSense	0
J1939 Park Brake Auto Neutral	0
Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
Front Axle & Equipment	
Dana Spicer D2000 Front Axle rated 18K	120
Front brakes included w/ front hub package.	0
Front Brake:Bendix 16.5x6 air brake package For 18K/20K non-driving front axle. Includes cast drum, 10 bolt iron LMS hub piloted hub, hubcap & slack adjusters.	113
Front Springs: taperleaf, 18K 2-stage with shocks and 54 in. spring length. T370 with 18K front axle only. 16mm frame fasteners.	172
Dual power steering gear: 18/20K	77
Power Steering Cooler: Radiator mounted air to oil 2007+ engines only. 2899362 is optional w/ 2006 or 2007 engines.	11
Rear Axle & Equipment	
DANA S30-190E 30K 74" TRACK	210
Rear Axle Ratio - 6.14.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
Single rear brakes included w/rear hub package.	0
30K air brake package includes 16-1/2x7 in. brakes, cast drums, iron 10-bolt hub pilot hubs and slack adjusters.	0
Spring Brake: 3036 single.	8
Bendix 4S/4M anti-lock brake system.	0
DIFF LOCK	28
Rear suspension: single Reyco 79KB multileaf 31K. 28K spring plus helper. Laden height 8.9 inches, unladen height 11.7 inches. Not available with shocks or swaybars. Not rear air disc brake compatible.	196
Rear axle stabilizer bar for Reyco 79KB.	66
Heavy-duty rear suspension crossmembers for Reyco 79KB replacing T3 standard.	41

Tires & Wheels

Front tires: Bridgestone M860A 315/80R22.5 20PR. 42.8 in. diameter, all position. 19.9 in. SLR.	94
Rear tires: Bridgestone M799 12R22.5 16PR. 43.3 in. diameter, drive. 20.1 in. SLR.	108
Rear Tire Quantity: 4	0
Front wheel: Accuride 29300 22.5x9 steel Steel Armor[TM] powder coat, hub pilot mount. 10000lb. maximum rating. 5-hand holes. Not air disc brake compatible.	80
Rear wheel: Accuride 50344 22.5x8.25 steel Steel Armor[TM] powder coat, hub pilot mount. Heavy-duty 5 hand-hole hub pilot mount. Code is priced per pair of wheels.	40
Wheelguards: all axles.	2
Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
Rear Wheel/Rim Quantity: 4	0

Frame & Equipment

Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 285in. to 336 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	340
Bumper: Aerodynamic, Painted. Requires a bumper setting code.	0
40.9 in. Bumper setting. Requires a bumper code.	0
Removable Front Tow Hooks: 2.	15
Front mudflaps.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
Custom Frame Layout: one chassis N6390 NEED AIR TANKS MOUNTED IN FRAM N6391 RAIL, BACK OF FUEL TANK MOUNT, N6392 AND HIGHER THAN A MIN. OF 13' N6393 OFF THE GROUND	0
Battery box cantilever aluminum BOC w/ fiberglass cover.	0
Battery box location: LH Side.	0
T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under.	0
Two bolted aluminum crossmember for center frame: Replacing T3 standard.	-22
Two bolted aluminum crossmembers for rear frame: Replacing T3 standard.	-22
One bolted rear cab crossmember: Replacing T3 standard.	17
Square end-of-frame w/ bolted crossmember non-towing.	41
Fuel Tanks & Equip	
Fuel Tank: 75 US gallon 22in. aluminum under replace. Class 8 fuel tank includes an anti-siphon device on the filler neck.	-11
Small round DEF tank. 11 gallons of useable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
Standard DEF to fuel fill ratio: 2:1 or greater.	0
DEF tank location is on the RH.	0
Location: 75 gal fuel tank LH under cab	0
Cab & Equipment	
Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
Cab door bearing blocks, top & bottom.	0
Hood: Sloped aerodynamic hood includes grill & separate bumper.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
Adjustable telescoping tilt steering column.	10
5 sets of keys. Replaces standard 2 sets of keys.	0
Information for customer-installed PTO Chelsea 277. 10-bolt. Available only with Allison 3000/4000 series transmissions.	0
Switch & Wiring for Customer-Installed PTO. Electric over hydraulic PTO. Includes switch guard. Wiring is routed to LH frame for connection to the customer installed PTO. No air controls are provided with this code.	0
Two spare switches: Wired to power.	0
Gauge: Dash mounted air filter restriction gauge.	0
KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
Driver seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	2
Rider seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	33
Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
Solid post antenna: Mounted on LH cowl. Replaces top-of-cab antenna. Recommended for dump trucks, loggers, & where overcab clearance is limited.	0

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



Description	Weight
Dash mounted CB assembly: W/leads & antennas. Includes dual antenna leads & dual antennas.	4
Self cancelling turn signal: W/head light dimmer switch .	0
Grabhandle LH inside door frame above dash.	0
Grabhandle RH inside door frame above dash.	2
Grabhandle LH w/ short extension over door.	4
Grabhandle RH w/ short extension over door.	4
DAYLITE DOOR: LH/RH INCL RH PEEPER WINDOW	0
Single Rectangular Air Horn 23 in. LH Top of Roof Includes Air Horn Cover.	6
Look-Down, Pass. Door, Stainless 8.5x4.4	0
Mirror: Dual Kenworth aerodynamic heated motorized 7 in. x 13 in. mirror w/ chrome shell. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8 1/2 ft load width. Switch located on door pad.	0
Rear Cab Stationary Window 17 in. x 36 in.	0
Electric-powered LH & RH door window lifts. Switch located on door.	0
Exterior aerodynamic sunvisor w/ integral marker lights.	6

Lights & Instruments

Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
Marker Lights: Five aerodynamic mounted in sunvisor.	0
Turn Signal Lights: Mounted on fender	0
Turn Signal Flasher: Kysor solid state.	0
Switch & Wiring for Customer-installed Floodlight w/o electrical pass-through - 1st set. Wire coiled BOC/BOS.	0
Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
Switch & Wiring: Customer-installed dual beacon lights w/o insulators. Coiled wire behind dash.	1
Daytime Running Lamps.	0
Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4
Body Builder Lighting Harness Coiled End Of Frame For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10



	Description	Weight
	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Breakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipment	Air Dryer: Bendix AD-IS heated.	0
	Full truck kit: Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.	15
	Locate air dryer outside RH rail BOC. This code requires the use of a custom frame layout code.	0
	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0
Extended Warranty	Medium-duty Warranty: 1-year/unlimited mi.	0
Miscellaneous	GHG Secondary Manufacturer: Does Not Apply	0
	Additional lead time required for off highway & /or specialty component truck.	0
	Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
	One 5 lb. dry chemical type fire extinguisher mounted outboard of driver seat. Class ABC.	11
Paint	Paint color number.	0
	N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK N97700 BUMPER L0006 WHITE	
	Bumper Painted Color A	0
	Day Cab Standard Paint	0
	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/17/2016 1:53:31 PM	Incomplete	Model Number:	T300 Series Conventional.
Effective Date:	Jan 1, 2016		Quote/DTPO/CO:	Q25385224
Prepared by:	Administrator		Version Number:	37.10

Body Spec

Name / Address
ERIE COUNTY WATER AUTHORITY 330 UNION ROAD CHEEKTOWAGA, NY.14227

Customer Contact	Customer Phone	Customer Fax

Item	Description	Qty	Cost	Total
EQUIPMENT	12-FT STEEL DUMP BODY MODEL# BRANDON 36 SIDES-42 GATE CAB SHIELD ONE CENTER COAL DOOR DOUBLE ACTING HOIST CYLINDER ELECTRIC VIBRATOR FOR DUMP BODY AIR GATE SHOVEL HOLDER LADDER W/STEPS WOOD SIDE BOARDS HARDWOOD BUMPER BOARDS (MNT-BOTTOM RUB RUB RAILS) LED STOP/TURN, AMBER FLASHERS EACH REAR POST REAR HITCH PLATE, W/25-TON PINTLE HOOK, SAFETY D-RINGS, CHASSIS SUPPLIED TRAILER PLUG AND GLAD HANDS MUD FLAPS FRONT AND REAR OF REAR TIRES PTO/PUMP TRANS AIR CONTROL FOR DUMP MNT ON FLOOR CONSOLE AIR TAILGATE CONTROL W/DUMP CONSOLE BODY PAINTED BLUE INSTALLED			

Subtotal

Sales Tax (8.75%) \$0.00

Total

Phone #	Fax #

I have reviewed and in agreement with the pricing associated with this order. By signing this quote I hereby authorize to proceed with order.

Signature _____

- 1) ENGINE WARRANTY PROTECTION PLAN 1 5YRS/100K/UNLIMITED HOURS INCLUDING AFTERTREATMENT AND TOW
- 2) ALLISON WARRANTY 3 YEARS BASE AND 2 YEARS EXTENDED
- 3) A MODIFIED BATTERY BOX WHICH IS 2-3" SHORTER THAT STD INCLUDED IN BASE.