

Town of Ashford
9377 Route 240
West Valley, NY 14171

Specifications for (1) 2017 10 Wheel Cab and Chassis

Vehicle Configuration
WESTERN STAR 4700 SET-FORWARD FRONT AXLE CHASSIS
2017 MODEL YEAR
SET FORWARD AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK
LH PRIMARY STEERING LOCATION
TRUCK/TRAILER CONFIGURATION
DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)
CONSTRUCTION SERVICE
GOVERNMENT BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
EXPECTED FRONT AXLE(S) LOAD : 22000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 68000.0 lbs
EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs
FRONT PLOW/END DUMP BODY
Engine and Equipment
DETROIT DD13 12.8L 470 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM
ENABLE AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE
2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG17
2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)
NO 2013 ENGINE ESCALATOR
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
ONE PIECE VALVE COVER
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER WITH SAFETY ELEMENT AND INSIDE/OUTSIDE AIR WITH SNOW DOOR
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES
BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL
LH BATTERY BOX MOUNTED AS FAR AFT AS POSSIBLE, NO GREATER THAN 60 INCHES BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE

AIR COMPRESSOR DISCHARGE LINE
ELECTRONIC ENGINE INTEGRAL WARNING AND DERATE PROTECTION SYSTEM
JACOBS COMPRESSION BRAKE
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH
10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT
STANDARD CURVE BRIGHT UPPER STACK(S)
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP
13 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING
NON-POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD
BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR
FULL FLOW OIL FILTER
1500 SQUARE INCH ALUMINUM RADIATOR
MOUNTING FOR FIREWALL MOUNTED SURGE TANK
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES
HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER
NO OIL PREHEATER
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR
ALUMINUM FLYWHEEL HOUSING
DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH
Transmission and Equipment
ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV
ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 3, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR, BLUNT CUT, MOUNTED BETWEEN DRIVER AND PASSENGER SEATS
CUSTOMER INSTALLED CHELSEA 277 SERIES PTO
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED
TRANSMISSION PROGNOSTICS - ENABLED 2013
WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)
Front Axle and Equipment
MFS-20-133A 22,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE
MERITOR 16.5X6 Q+ 22,000# CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
SKF SCOTSEAL PLUS XL FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
STANDARD SPINDLE NUTS FOR ALL AXLES
HALDEX AUTOMATIC FRONT SLACK ADJUSTERS WITH STAINLESS STEEL CLEVIS PINS
STANDARD KING PIN BUSHINGS
TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR
POWER STEERING PUMP
4 QUART POWER STEERING RESERVOIR
OIL/AIR POWER STEERING COOLER
SYNTHETIC 50W FRONT AXLE LUBE
Front Suspension
23,000# FLAT LEAF FRONT SUSPENSION
THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION
FRONT SHOCK ABSORBERS
Rear Axle and Equipment
RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE
5.38 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING
SPL250HD XL DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES
SPL170 XL DANA SPICER INTERAXLE DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AXLE VALVE AND (1) REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY
CONMET CAST IRON REAR BRAKE DRUMS
REAR BRAKE DUST SHIELDS
SKF SCOTSEAL PLUS XL REAR OIL SEALS
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS WITH STAINLESS STEEL CLEVIS PINS
SYNTHETIC 75W-90 REAR AXLE LUBE
Rear Suspension
HENDRICKSON HAULMAAX REAR SUSPENSION @ 46,000#
HENDRICKSON HAULMAAX/ULTIMAAX - 10.50" RIDE HEIGHT
54 INCH AXLE SPACING
HENDRICKSON HN, HAULMAAX AND ULTIMAAX SERIES STEEL BEAMS WITH BAR PIN
FORE/AFT AND TRANSVERSE CONTROL RODS

REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)
Brake System
WABCO 4S/4M ABS WITH TRACTION CONTROL
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER
WABCO OIL COALESCING FILTER FOR AIR DRYER
AIR DRYER MOUNTED OUTBOARD ON RH RAIL
STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION
CLEAR FRAME RAIL 36 INCHES FROM BACK OF CAB INSIDE/OUTBOARD AND BELOW RH FRAME RAIL
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER TO WET TANK; DRAIN VALVE CABLES ON ALL OTHER TANKS
Trailer Connections
AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME
Wheelbase & Frame
5500MM (217 INCH) WHEELBASE
1/2X3.64X11-7/8 INCH STEEL FRAME (12.7MMX301.6MM/0.5X11.88 INCH) 120KSI
PARTIAL INNER FRAME REINFORCEMENT AT FRONT SUSPENSION
BODY COMPANY INSTALLED ADDITIONAL FRONT FRAME REINFORCEMENT FOR SNOW PLOW
1600MM (63 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 61 INCH TO 70 INCH
24 INCH INTEGRAL FRONT FRAME EXTENSION
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 135.78 in
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 132.78 in
CALC'D FRAME LENGTH - OVERALL : 331.69
CALC'D SPACE AVAILABLE FOR DECKPLATE : 135.78 in
CALCULATED FRAME SPACE LH SIDE : 40.66 in
CALCULATED FRAME SPACE RH SIDE : 85.54 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CROSSMEMBER BACK OF TRANSMISSION
STANDARD MIDSHIP #1 CROSSMEMBER(S)
STANDARD REARMOST CROSSMEMBER
HEAVY DUTY SUSPENSION CROSSMEMBER
STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER
Chassis Equipment
OMIT FRONT BUMPER, CUSTOMER INSTALLED SPECIAL BUMPER, DOES NOT COMPLY WITH FMCSR 393.203
FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS
Fuel Tanks
100 GALLON/378 LITER ALUMINUM FUEL TANK - LH
25 INCH DIAMETER FUEL TANK(S)

PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
NO FUEL COOLER
Tires // Hubs // Wheels
MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES
MICHELIN XDE M/S 11R24.5 16 PLY RADIAL REAR TIRES
CONMET PRESET PLUS IRON FRONT HUBS
CONMET PRESET PLUS IRON REAR HUBS
ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS
ALCOA LVL ONE 98363X 24.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS
FRONT WHEEL MOUNTING NUTS
REAR WHEEL MOUNTING NUTS
NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES
Cab Exterior
110 INCH BBC STEEL CONVENTIONAL CAB
WESTERN STAR STAINLESS STEEL CAB SKIRT
AIR CAB MOUNTS WITH CHECK VALVE
NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE
FRONT FENDERS
2 INCH FENDER EXTENSIONS
LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERTS AND RH INTERIOR GRAB HANDLE MOUNTED TO A POST
STATIONARY BRIGHT FINISH GRILLE
CHROME HOOD MOUNTED AIR INTAKE GRILLE
GALVANEALD STEEL SEVERE SERVICE CAB
FIBERGLASS HOOD WITH ACCESS HATCHES
TUNNEL/FIREWALL LINER
DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
SINGLE ELECTRIC HORN
DUAL HORN SHIELDS
DOORS AND IGNITION KEYED THE SAME
REAR LICENSE PLATE MOUNT END OF FRAME
SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS
SINGLE RECTANGULAR SEALED BEAM HEADLIGHTS WITH BRIGHT BEZELS
(5) AMBER MARKER LIGHTS
WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH DUAL CONNECTIONS AT BUMPER
WIRING AND SWITCH ONLY FOR CUSTOMER FURNISHED FOG LIGHTS
INDIVIDUAL LED STOP/TURN/BACKUP LIGHTS GROMMET MOUNTED BELOW RAIL
STANDARD FRONT TURN SIGNAL LAMPS
DUAL MEKRA AERO BRIGHT FINISH HEATED DUAL AXIS 1-PIECE MOTORIZED MIRRORS WITH LIGHTS, LH AND RH REMOTE AND INTEGRAL CONVEX MIRRORS
CAB MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
DUAL MEKRA BRIGHT FINISH HEATED CONVEX MIRRORS WITH MANUAL ADJUSTMENT AND DUAL AXIS FOR 1-PIECE PRIMARY MIRRORS

RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER
STAINLESS STEEL EXTERIOR SUN VISOR
17.5X35 INCH TINTED REAR WINDOW
TINTED DOOR GLASS
RH AND LH ELECTRIC POWERED WINDOWS
LOWER RH DOOR WINDOW WITH FRESNEL LENS
2-PIECE TINTED CURVED GASKET MOUNTED HEATED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, MOUNTED UNDER CAB, WITH REMOTE FILL
Cab Interior
SMOKY MOUNTAIN GRAY VINYL PREMIUM INTERIOR
BLACK HARD TRIM
PREMIUM LEFT HAND DOOR TRIM WITH CHERRY ACCENT
PREMIUM RIGHT HAND DOOR TRIM WITH CHERRY ACCENT
BLACK MATS WITH DOUBLE INSULATION
DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE
FORWARD ROOF MOUNTED CONSOLE
PASSENGER SIDE WING DASH MOUNTED GLOVE BOX WITH LOCKING DOOR
14"X7.75" DOCUMENT POUCH MOUNTED ON BACK WALL BETWEEN SEATS
LH AND RH DOOR MAP POCKETS
COAT HOOK ON RH BACKWALL OF CAB
(1) DOUBLE CUP HOLDER WITH CELL PHONE HOLDER LH OR RH DASH
TWO-TONE CHARCOAL UPPER/COOL GRAY LOWER SOFT TOUCH WING DASH WITH BLACK DRIVER SIDE COSMETIC UNDER DASH COVER
STANDARD WIRING
5 LB. FIRE EXTINGUISHER
HEATER, DEFROSTER AND AIR CONDITIONER WITH COSMETIC COVER
HVAC DUCTING WITH DUST/ODOR MAIN FRESH AIR FILTER AND OUTSIDE PRE-FILTER
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR
RADIATOR MOUNTED AIR CONDITIONER CONDENSER
BINARY CONTROL, R-134A
ADDITIONAL CAB SIDEWALL INSULATION
CIRCUIT FUSES
DOOR ACTIVATED DOME LIGHT, UNDER DASH LIGHT AND LH AND RH DOOR MOUNTED COURTESY LIGHTS
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS
(1) 12 VOLT POWER SUPPLY IN DASH
TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB
PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER
BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT
DUAL DRIVER AND PASSENGER SEAT ARMRESTS
MORDURA CLOTH DRIVER SEAT
MORDURA CLOTH PASSENGER SEAT
3 POINT DRIVER AND PASSENGER SEAT BELT RETRACTORS
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

2-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL(S)
DRIVER AND PASSENGER INTERIOR SUN VISORS
Instruments & Controls
NON-ADJUSTABLE SUSPENDED PEDALS
STAR GAUGES WITH BRIGHT BEZELS
FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH DRIVER INSTRUMENT PANEL
FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH CENTER INSTRUMENT PANEL
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM
(1) SINGLE BRAKE APPLICATION AIR GAUGE
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES
DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS
87 DB TO 112 DB SELF-ADJUSTING BACKUP ALARM
CRUISE CONTROL SWITCHES IN THE CENTER PANEL
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
WARNING LAMP/LIGHT BAR DISPLAY, NON-DATA LINKED
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE
FUEL FILTER RESTRICTION INDICATOR
EMISSIONS LIMITED IDLE ADJUST
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
OUTSIDE AIR TEMPERATURE GAUGE WITH FAHRENHEIT AND CELSIUS DISPLAY MOUNTED IN OVERHEAD CONSOLE
(1) DASH MOUNTED PTO SWITCH WITH INDICATOR LAMP
ELECTRIC ENGINE OIL PRESSURE GAUGE
AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, USB, FRONT AND REAR AUXILIARY INPUTS AND J1939
ROOF/OVERHEAD CONSOLE MOUNTED RADIO
(4) RADIO SPEAKERS IN CAB
AM/FM ANTENNA MOUNTED ON LH FRONT A-PILLAR
POWER AND GROUND WIRING FOR CB RADIO IN OVERHEAD CONSOLE
MULTI-BAND AM/FM/WB/CB LH MIRROR MOUNTED ANTENNA SYSTEM
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITH ODOMETER
STANDARD VEHICLE SPEED SENSOR WITH ADDITIONAL SIGNAL FOR CUSTOMER USE LOCATED BETWEEN DRIVER AND PASSENGER SEATS
ELECTRONIC 3000 RPM TACHOMETER WITH HOUR METER
DETROIT CONNECT VIRTUAL TECHNICIAN CONNECTIVITY PACKAGE (DETROIT ENGINES ONLY)
2 YEARS DETROIT CONNECT VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR IGNITION CONTROLLED EXTRA SWITCHES WITH INDICATOR LIGHT, 10 AMPS, WIRED BETWEEN DRIVER AND PASSENGER SEATS
BW TRACTOR PROTECTION VALVE
TRAILER HAND CONTROL BRAKE VALVE
2 INCH VOLTMETER
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY
CAB MARKER LIGHT AND HEADLIGHT SWITCH WITH SEPARATE SWITCH AND TERMINALS FOR CUSTOMER FURNISHED SNOW PLOW LIGHTS AND TURN SIGNALS
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
VSM NON CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITH BRAKE OVERRIDE

PACIFIC INSIGHT ELECTRONIC FLASHER

Design and Color

PAINT: ONE SOLID COLOR

CAB COLOR A: 00782250EB CRYSTAL CLARET RED MET ELITE BC

CAB INTERIOR PAINTED SAME AS CAB COLOR

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

FENDER AND INTERIOR CAB FLOOR UNDERCOATING

Certification//Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Extended Warranty

EW4 DD13 VOC \$0 DEDUCTIBLE 7 YEAR/250000 MILES FULL COVERAGE

TOWING: 5 YEAR/UNLIMITED MILES/KM EXTENDED TOWING COVERAGE \$550 CAP

ALLISON 4500 RDS SERIES TRANSMISSION EXTENDED WARRANTY, 5 YEARS/UNLIMITED MILES X

Installed Option

RIGHT FRONT SPRING BOOST FOR WING PLOW APPLICATION