

New York State OMH T16040016

Plow Truck Specs

**2016 F-SERIES SD**

Ord PEP: 630A  
F3F F350 4X4CHAS/CS  
425 50 STATE EMISS  
141" WHEELBASE  
473 SNOW PLOW PKG  
Z1 OXFORD WHITE  
A VNYL 40/20/40  
52B BRAKE CONTROLLR  
S STEEL  
64F STEEL WHLS-18"  
.XL Trim  
572 .AIR CONDITIONER  
.AM/FM STER/CLK  
996 6.2L EFI V8 ENG  
44P 6-SPD AUTOMATIC  
TDX LT275/70BSWAT18  
X37 3.73 REG AXLE  
10200# GVWR PKG  
41H ENG BLK HEATER

Plow Package:

Smith Metalworks 9' x 84" Stainless Steel Platform  
T304 Stainless Steel Construction Throughout  
3/16" 5" Boxed Long Rails  
3/16" 3" Crossmembers on 12" Centers  
3/16" Smooth Stainless Steel Floor  
3/16" 4" Formed Channel Outrails  
3/16" Stake Pockets Sides and Rear  
1/4" x 2.5" Stainless Banding Rail (Sides & Rear)  
3/16" Rear Apron with Oval Light Cutouts  
Integrated License Plate Cutout in Rear Apron  
10 Gauge Reinforced Bulkhead with Window  
3/16" Rectangular Tube Welded to Longrails  
3/16" Rectangular Tube Welded to Crossmembers  
LED Light Kit Included  
S/T/T, Backups, Markers  
Ecco Model E92020 Clear LED Work Light  
12 LEDs, 980 Lumens, 12-24 VDC, 1.5Amps  
(2) Mounted to Bulkhead Aiming Rearward  
(2) Mounted to Salter Aiming at Chute  
Wired to Upfitter Switches  
Rooftop Mounted LED Mini Bar

PSE Model SHL 10CAW  
Permanent Mount, Flashes White and Amber  
Wired to Upfitter Switches  
Four Corner Strobes Installed  
Ecco Model 9021AA Front Hide-a-way Amber Strobes  
PSE Model OVLALS1H Rear Oval Amber Strobes  
Wired to Upfitter Switches  
102dB Back Up Alarm installed  
Rear Hitch Plate Installed  
3/8" Formed Plate, Welded and Gusseted to Rear Frame  
2 5/16" Pintle Ball Combo Hitch  
D Rings and Seven Way Plug Installed  
8'6" Fisher Extreme Vee 1 Stainless Snowplow Installed  
Handheld Control and Cutting Edge Standard  
Intensifire Halogen Headlights Standard  
Wear Shoes Included  
8' Fisher Stainless Steel Steelcaster Hopper Spreader  
8' Hopper Length, 2.0 Cubic Yard Capacity  
16 Gauge T201 Stainless Steel Construction  
11HP Honda Gas Engine  
96" x 50" x 40" Dimensions  
15.5" Spinner Diameter  
16.5" Conveyor Width  
In Cab Electric Start with Throttle Control  
Inverted Vee and Topscreen Standard