

# ***City of North Tonawanda***

## **Mini-Bid T16040024**

**Freightliner M2 106 with Heil DURAPACK 5000 Rear Load Packer**



# S P E C I F I C A T I O N

## Description

### Vehicle Configuration

M2 106 CONVENTIONAL CHASSIS  
2017 MODEL YEAR SPECIFIED  
SET BACK AXLE - TRUCK  
STRAIGHT TRUCK PROVISION  
LH PRIMARY STEERING LOCATION

### General Service

TRUCK CONFIGURATION  
DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)  
REFUSE SERVICE  
GOVERNMENT BUSINESS SEGMENT  
DRY BULK COMMODITY  
TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS  
MAXIMUM 8% EXPECTED GRADE  
MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE  
MEDIUM TRUCK WARRANTY  
EXPECTED FRONT AXLE(S) LOAD : 16000.0 lbs  
EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs  
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 56000.0 lbs

### Truck Service

REFUSE, SIDE LOAD OR REAR PACKER BODY - UNLOADS IN A LANDFILL  
EXPECTED TRUCK BODY LENGTH : 20.0 ft  
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in

### Engine

CUM ISL 330 HP @ 2000 RPM, 2200 GOV RPM, 1000 LB/FT @ 1400 RPM

### Electronic Parameters

75 MPH ROAD SPEED LIMIT  
CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT  
PTO MODE ENGINE RPM LIMIT - 1100 RPM  
PTO RPM WITH CRUISE SET SWITCH - 700 RPM  
PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM  
PTO MODE CANCEL VEHICLE SPEED - 5 MPH  
PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND  
PTO MINIMUM RPM - 700  
REGEN INHIBIT SPEED THRESHOLD - 5 MPH

### Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG17 BUT NOT FINAL GHG17 CONFIGURATION  
2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)  
STANDARD OIL PAN

## Description

ENGINE MOUNTED OIL CHECK AND FILL  
ONE PIECE VALVE COVER  
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER  
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE  
(2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES  
BATTERY BOX FRAME MOUNTED  
STANDARD BATTERY JUMPERS  
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB  
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN  
NON-POLISHED BATTERY BOX COVER  
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE  
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR  
AIR COMPRESSOR DISCHARGE LINE  
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM  
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH  
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE  
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH  
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT  
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP  
6 GALLON DIESEL EXHAUST FLUID TANK  
100 PERCENT DIESEL EXHAUST FLUID FILL  
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION  
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING  
STANDARD DIESEL EXHAUST FLUID TANK CAP  
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD  
HORTON DRIVEMASTER ON/OFF FAN DRIVE  
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED  
CUMMINS SPIN ON FUEL FILTER  
COMBINATION FULL FLOW/BYPASS OIL FILTER  
FLEETGUARD PLAIN COOLANT FILTER  
1100 SQUARE INCH ALUMINUM RADIATOR  
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT  
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT  
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES  
RADIATOR DRAIN VALVE  
LOWER RADIATOR GUARD  
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER  
BLACK PLASTIC ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR  
ALUMINUM FLYWHEEL HOUSING  
ELECTRIC GRID AIR INTAKE WARMER  
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH

## Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

## Description

### Transmission Equipment

ALLISON VOCATIONAL PACKAGE 142 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL RDS

ALLISON VOCATIONAL RATING FOR REFUSE APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED

DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES

VEHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT END OF FRAME

ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR MOUNTED BACK OF CAB

CUSTOMER INSTALLED CHELSEA 277 SERIES PTO

PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK

TRANSMISSION OIL CHECK AND FILL WITH CROSSOVER TO CLEAR LH PTO AND DIRECT MOUNT PUMP

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

### Front Axle and Equipment

DETROIT DA-F-16.0-5 16,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE

MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

SKF SCOTSEAL PLUS XL FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

STANDARD SPINDLE NUTS FOR ALL AXLES

HALDEX AUTOMATIC FRONT SLACK ADJUSTERS

TRW TAS-85 POWER STEERING

POWER STEERING PUMP

2 QUART SEE THROUGH POWER STEERING RESERVOIR

OIL/AIR POWER STEERING COOLER

SYNTHETIC 75W-90 FRONT AXLE LUBE

### Front Suspension

16,000# FLAT LEAF FRONT SUSPENSION

GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION

NO FRONT SUSPENSION SPRING BRACKET OPTIONS

FRONT SHOCK ABSORBERS

### Rear Axle and Equipment

MT-40-14XP 40,000# R-SERIES TANDEM REAR AXLE

6.43 REAR AXLE RATIO

IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING

MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES

## Description

MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES  
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES  
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE  
BLINKING LAMP WITH EACH MODE SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF  
BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH  
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES  
NON-ASBESTOS REAR BRAKE LINING  
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)  
CONMET CAST IRON REAR BRAKE DRUMS  
REAR BRAKE DUST SHIELDS  
SKF SCOTSEAL PLUS XL REAR OIL SEALS  
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS  
HALDEX AUTOMATIC REAR SLACK ADJUSTERS  
SYNTHETIC 75W-90 REAR AXLE LUBE

## Rear Suspension

TUFTRAC 40,000# REAR SPRING SUSPENSION  
TUFTRAC STANDARD RIDE HEIGHT  
AXLE CLAMPING GROUP  
54 INCH AXLE SPACING  
FORE/AFT AND TRANSVERSE CONTROL RODS  
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)

## Brake System

AIR BRAKE PACKAGE  
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL  
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES  
FIBER BRAID PARKING BRAKE HOSE  
STANDARD BRAKE SYSTEM VALVES  
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM  
STD U.S. FRONT BRAKE VALVE  
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE  
BW AD-9SI BRAKE LINE AIR DRYER WITH HEATER  
AIR DRYER MOUNTED INBOARD ON LH RAIL  
STEEL AIR BRAKE RESERVOIRS MOUNTED INSIDE RAIL  
PULL CABLES ON ALL AIR RESERVOIR(S)

## Trailer Connections

UPGRADED CHASSIS MULTIPLEXING UNIT  
UPGRADED BULKHEAD MULTIPLEXING UNIT  
NO HIGH CURRENT TRAILER/BODY CABLE

## Wheelbase & Frame

5650MM (222 INCH) WHEELBASE  
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI  
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT  
1600MM (63 INCH) REAR FRAME OVERHANG

## Description

FRAME OVERHANG RANGE: 61 INCH TO 70 INCH  
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 156.45 in  
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 153.45 in  
CALC'D FRAME LENGTH - OVERALL : 314.39  
CALC'D SPACE AVAILABLE FOR DECKPLATE : 156.45 in  
CALCULATED FRAME SPACE LH SIDE : 84.21 in  
CALCULATED FRAME SPACE RH SIDE : 126.2 in  
SQUARE END OF FRAME  
FRONT CLOSING CROSSMEMBER  
LIGHTWEIGHT HEAVY DUTY ALUMINUM ENGINE CROSSMEMBER  
STANDARD MIDSHIP #1 CROSSMEMBER(S)  
STANDARD REARMOST CROSSMEMBER  
HEAVY DUTY SUSPENSION CROSSMEMBER

## Chassis Equipment

THREE-PIECE 14 INCH PAINTED STEEL BUMPER WITH COLLAPSIBLE ENDS  
FRONT TOW HOOKS - FRAME MOUNTED  
BUMPER MOUNTING FOR SINGLE LICENSE PLATE  
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS  
GRADE 8 THREADED HEX HEADED FRAME FASTENERS

## Fuel Tanks

50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH  
RECTANGULAR FUEL TANK(S)  
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS  
FUEL TANK(S) FORWARD  
PLAIN STEP FINISH  
FUEL TANK CAP(S)  
ALLIANCE FUEL FILTER/WATER SEPARATOR WITH HEATED BOWL AND PRIMER PUMP  
EQUIFLO INBOARD FUEL SYSTEM  
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE

## Tires

GOODYEAR G291 315/80R22.5 18 PLY RADIAL FRONT TIRES  
GOODYEAR G182 RSD 11R22.5 16 PLY RADIAL REAR TIRES  
GOODYEAR G291 315/80R22.5 18 PLY RADIAL SPARE FRONT TIRE  
GOODYEAR G182 RSD 11R22.5 16 PLY RADIAL SAPRE REAR TIRE

## Hubs

CONMET PRESET PLUS IRON FRONT HUBS  
CONMET PRESET PLUS IRON REAR HUBS

## Wheels

ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS  
ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2-HAND HD STEEL DISC REAR WHEELS  
ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC SPARE WHEEL  
ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2-HAND HD STEEL DISC ADDITIONAL SPARE WHEEL  
FRONT WHEEL MOUNTING NUTS  
REAR WHEEL MOUNTING NUTS

**Description**

---

NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES

**Cab Exterior**

106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB  
AIR CAB MOUNTS  
NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE  
2-1/2 INCH FENDER EXTENSIONS  
NO GRAB HANDLES  
HOOD MOUNTED CHROMED PLASTIC GRILLE  
CHROME HOOD MOUNTED AIR INTAKE GRILLE  
FIBERGLASS HOOD  
SINGLE 14 INCH ROUND POLISHED AIR HORN ROOF MOUNTED  
SINGLE ELECTRIC HORN  
SINGLE HORN SHIELD  
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME  
REAR LICENSE PLATE MOUNT END OF FRAME  
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL  
(5) AMBER MARKER LIGHTS  
DAYTIME RUNNING LIGHTS  
INTEGRAL STOP/TAIL/BACKUP LIGHTS  
STANDARD FRONT TURN SIGNAL LAMPS  
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS  
DOOR MOUNTED MIRRORS  
102 INCH EQUIPMENT WIDTH  
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS  
RH AND LH 8 INCH STAINLESS STEEL FENDER MOUNTED CONVEX MIRRORS WITH TRIPOD BRACKETS  
STANDARD SIDE/REAR REFLECTORS  
63X14 INCH TINTED REAR WINDOW  
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS  
MANUAL DOOR WINDOW REGULATORS  
TINTED WINDSHIELD  
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED

**Cab Interior**

OPAL GRAY CLOTH INTERIOR  
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR  
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR  
BLACK MATS WITH SINGLE INSULATION  
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING  
IN DASH STORAGE BIN  
(2) CUP HOLDERS LH AND RH DASH  
GRAY/CHARCOAL FLAT DASH  
SMART SWITCH EXPANSION MODULE  
5 LB. FIRE EXTINGUISHER  
HEATER, DEFROSTER AND AIR CONDITIONER  
STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE  
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH

## Description

STANDARD HEATER PLUMBING  
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR  
BINARY CONTROL, R-134A  
STANDARD INSULATION  
SOLID-STATE CIRCUIT PROTECTION AND FUSES  
12V NEGATIVE GROUND ELECTRICAL SYSTEM  
DOME DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF  
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS  
(1) 12 VOLT POWER SUPPLY IN DASH  
TRIANGULAR REFLECTORS WITHOUT FLARES  
BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION  
2 MAN TOOL BOX MID BACK NON SUSPENSION PASSENGER SEAT  
LH AND RH INTEGRAL DOOR PANEL ARMRESTS  
BLACK MORDURA CLOTH DRIVER SEAT COVER  
GRAY MORDURA CLOTH PASSENGER SEAT COVER  
3 POINT DRIVER AND PASSENGER AND 2 POINT CENTER FRONT SEAT BELT RETRACTORS  
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN  
4-SPOKE 18 INCH (450MM) STEERING WHEEL  
DRIVER AND PASSENGER INTERIOR SUN VISORS

## Instruments & Controls

WOODGRAIN DRIVER INSTRUMENT PANEL  
WOODGRAIN CENTER INSTRUMENT PANEL  
BLACK GAUGE BEZELS  
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM  
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES  
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS  
PRECO 1040 87 DB TO 112 DB AUTOMATIC SELF-ADJUSTING BACKUP ALARM  
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL  
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION  
OFF/RUN/START/ACCESSORY  
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED  
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH  
2 INCH ELECTRIC FUEL GAUGE  
PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE  
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE  
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE  
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY  
CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS  
NO LANE DEPARTURE WARNING SYSTEM  
ELECTRIC ENGINE OIL PRESSURE GAUGE  
OVERHEAD INSTRUMENT PANEL  
AM/FM RADIO WITH FRONT AND REAR AUXILIARY INPUTS AND J1939  
DASH MOUNTED RADIO  
(2) RADIO SPEAKERS IN CAB  
POWER AND GROUND STUDS IN/UNDER DASH

## Description

MULTI-BAND AM/FM/WB/CB LH MIRROR MOUNTED ANTENNA SYSTEM  
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER  
STANDARD VEHICLE SPEED SENSOR  
ELECTRONIC 3000 RPM TACHOMETER  
IGNITION SWITCH CONTROLLED ENGINE STOP  
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY  
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY  
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH  
ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR  
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE  
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS  
NO MISCELLANEOUS GAUGES

## Design

PAINT: ONE SOLID COLOR

## Color

CAB COLOR A: L2620EB MED GREEN ELITE BC  
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT  
NO FUEL TANK CABINET PAINT  
POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
POWDER WHITE (N0006EA) SPARE WHEEL/RIM (PKWHT21, TKWHT21, W, TW)  
BUMPER PAINT: FP24812 ARGENT SILVER DUPONT FLEX  
STANDARD E COAT/UNDERCOATING

## Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

## Extended Warranty

EPA 2013 CUMMINS ISL ENGINE EXTENDED WARRANTY DC1, 5 YEARS/100,000 MILES/160 000 KM FEX  
EPA 2013 CUMMINS ISL ENGINE EXTENDED WARRANTY AFTERTREATMENT AT3, 5 YEARS/100,000  
MILES/160 000 KM FEX  
ALLISON 3000 RDS TRANSMISSION FOR REFUSE EXTENDED WARRANTY, 5 YEARS/UNLIMITED MILEAGE  
FEX

## **COMPACTION REAR LOADER**

Body Type: Refuse Body

Body Make: Heil

Body Model: DURAPACK 5000

2016 Model Year

High Compaction Rear Loader

25 Cubic Yard

3.94 Cubic Yard Hopper

Direct Mount Gear Pump

Hot Shift PTO W/ EOS

Multi-Function Lights LED Strobe/Turn Lamps

Left Hand Buzzer

Heavy Duty Contractors Package

Body Side Door with Step

Painted: White

Dual Control Valve Section w/ Control handles

Dual Perkins D6080 Tippers Installed

Perkins D6080 Tippers, Spares (2)