

Request for Comments #T16050006 – Town of Little Valley

Note: This is a Request for Comments. Please send any Comments directly to the Authorized User via email. Do not submit Bids at this time.

S P E C I F I C A T I O N P R O P O S A L

Description

Price Level

WESTERN STAR 4700 PRL-14T (EFF:10/05/15)

Data Version

SPECPRO21 DATA RELEASE VER 025

Vehicle Configuration

4700 SET-FORWARD FRONT AXLE CHASSIS
2017 MODEL YEAR SPECIFIED
SET FORWARD AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF
FRAME FOR TRUCK
LH PRIMARY STEERING LOCATION

General Service

TRUCK/TRAILER CONFIGURATION
DOMICILED, USA 50 STATES (INCLUDING
CALIFORNIA AND CARB OPT-IN STATES)
CONSTRUCTION SERVICE
GOVERNMENT BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN
TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
SMOOTH CONCRETE OR ASPHALT PAVEMENT -
MOST SEVERE IN-TRANSIT (BETWEEN SITES)
ROAD SURFACE
WESTERN STAR VOCATIONAL WARRANTY
EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs

Description

EXPECTED REAR DRIVE AXLE(S) LOAD :
46000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 66000.0 lbs
EXPECTED GROSS COMBINATION WEIGHT :
80000.0 lbs

Truck Service

PLOW TO BE PURCHASED FROM AND
INSTALLED BY A SEPARATE CONTRACTOR AT
A LATER DATE

Tractor Service

DUMP TRUCK – TO BE PURCHASED FROM AND
INSTALLED BY A SEPARATE CONTRACTOR AT
A LATER DATE

Engine

DETROIT DD13 12.8L 505 HP @ 1625 RPM, 1900
GOV RPM, 1850 LB/FT @ 975 RPM

Electronic Parameters

65 MPH ROAD SPEED LIMIT
CRUISE CONTROL SPEED LIMIT SAME AS ROAD
SPEED LIMIT
10 MINUTES IDLE SHUTDOWN WITH CLUTCH
AND SERVICE BRAKE OVERRIDE
10 MINUTES PTO SHUTDOWN WITH CLUTCH
AND BRAKE OVERRIDE
PTO MODE ENGINE RPM LIMIT - 1100 RPM
PTO MODE BRAKE OVERRIDE - SERVICE
BRAKE APPLIED OR PARK BRAKE NOT APPLIED
PTO RPM WITH CRUISE SET SWITCH - 800 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 800
RPM
ONE REMOTE PTO SPEED
REMOTE PTO SPEED 1 SETTING - 900 RPM
SOFT CRUISE CONTROL ENABLED
PTO MINIMUM RPM - 600
ENABLE AUTO ENGINE RPM ELEVATE FOR
EXTENDED IDLE

Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010
EPA/CARB/FINAL GHG17 CONFIGURATION

Description

2008 CARB EMISSION CERTIFICATION - CLEAN
IDLE (INCLUDES 6X4 INCH LABEL ON LOWER
FORWARD CORNER OF DRIVER DOOR)

NO 2013 ENGINE ESCALATOR

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

ONE PIECE VALVE COVER

SIDE OF HOOD AIR INTAKE WITH FIREWALL
MOUNTED DONALDSON AIR CLEANER WITH
SAFETY ELEMENT AND INSIDE/OUTSIDE AIR
WITH SNOW DOOR

DR 12V 160 AMP 36-SI BRUSHLESS
QUADRAMOUNT PAD ALTERNATOR WITH
REMOTE BATTERY VOLT SENSE

(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT
MAINTENANCE FREE 3375 CCA THREADED
STUD BATTERIES

BATTERY BOX FRAME MOUNTED

SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB

WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN

NON-POLISHED BATTERY BOX COVER

BW MODEL BA-921 19.0 CFM SINGLE CYLINDER
AIR COMPRESSOR WITH SAFETY VALVE

AIR COMPRESSOR DISCHARGE LINE

ELECTRONIC ENGINE INTEGRAL WARNING AND
DERATE PROTECTION SYSTEM

JACOBS COMPRESSION BRAKE

RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND DASH MOUNTED REGENERATION
REQUEST SWITCH

10 FOOT 06 INCH (126 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT

STANDARD CURVE BRIGHT UPPER STACK(S)

RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK

100 PERCENT DIESEL EXHAUST FLUID FILL

STANDARD DIESEL EXHAUST FLUID PUMP
MOUNTING

Description

NON-POLISHED ALUMINUM DIESEL EXHAUST
FLUID TANK COVER

LH MEDIUM DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION

STAINLESS STEEL AFTERTREATMENT
DEVICE/MUFFLER/TAILPIPE SHIELD

HORTON 2-SPEED DRIVEMASTER
POLAREXTREME FAN DRIVE

AUTOMATIC FAN CONTROL WITHOUT DASH
SWITCH, NON ENGINE MOUNTED

DDC SUPPLIED ENGINE MOUNTED FUEL
FILTER/FUEL WATER SEPARATOR WITH
WATER-IN-FUEL INDICATOR

FULL FLOW OIL FILTER

1500 SQUARE INCH ALUMINUM RADIATOR

MOUNTING FOR FIREWALL MOUNTED SURGE
TANK

ANTIFREEZE TO -34F, OAT (NITRITE AND
SILICATE FREE) EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT

CONSTANT TENSION HOSE CLAMPS FOR
COOLANT HOSES

HDEP VARIABLE SPEED COOLANT PUMP AND
NO OPTIONAL RADIATOR DRAIN VALVE

PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK
HEATER

NO OIL PREHEATER

CHROME ENGINE HEATER RECEPTACLE
MOUNTED UNDER LH DOOR

ALUMINUM FLYWHEEL HOUSING

DELCO 12V MOD 3.175-39MT+ OCP STARTER
WITH THERMAL PROTECTION AND
INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 4500 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV

ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES

Description

PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY

ELECTRONIC TRANSMISSION CUSTOMER
ACCESS CONNECTOR, BLUNT CUT, MOUNTED
BETWEEN DRIVER AND PASSENGER SEATS

CUSTOMER INSTALLED CHELSEA 277 SERIES
PTO

PTO MOUNTING, LH SIDE OF MAIN
TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN

PUSH BUTTON ELECTRONIC SHIFT CONTROL,
DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER,
FRAME MOUNTED

TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74
DROP SINGLE FRONT AXLE

BENDIX ADB22X-V AIR DISC FRONT BRAKES

NON-ASBESTOS FRONT BRAKE LINING

FRONT DISC BRAKE ROTORS

FRONT BRAKE DUST SHIELDS

SKF SCOTSEAL PLUS XL FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL

STANDARD SPINDLE NUTS FOR ALL AXLES

FRONT AIR DISC BRAKE INTERNAL ADJUSTERS

STANDARD KING PIN BUSHINGS

TRW THP-60 POWER STEERING WITH RCH45
AUXILIARY GEAR

POWER STEERING PUMP

4 QUART POWER STEERING RESERVOIR

OIL/AIR POWER STEERING COOLER

SYNTHETIC 75W-90 FRONT AXLE LUBE

Description

Front Suspension

20,000# FLAT LEAF FRONT SUSPENSION
THREADED SPRING PINS AND BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RT-46-160P 46,000# R-SERIES TANDEM REAR
AXLE
4.89 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
MXL 18N MERITOR EXTENDED LUBE MAIN
DRIVELINE WITH FULL ROUND YOKES
MXL 17N MERITOR EXTENDED LUBE
INTERAXLE DRIVELINE WITH FULL ROUND
YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE
LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DRIVER
CONTROLLED TRACTION DEVICE SWITCH
BENDIX ADB22X-V AIR DISC REAR BRAKES
NON-ASBESTOS REAR BRAKE LINING
STANDARD BRAKE CHAMBER LOCATION
REAR DISC BRAKE ROTORS
REAR BRAKE DUST SHIELDS
SKF SCOTSEAL PLUS XL REAR OIL SEALS
AIR DISC LONGSTROKE 2-DRIVE AXLES SPRING
PARKING CHAMBERS
REAR AIR DISC BRAKE INTERNAL ADJUSTERS
SYNTHETIC 75W-90 REAR AXLE LUBE

Rear Suspension

HENDRICKSON HAULMAAX REAR SUSPENSION
@ 46,000#
HENDRICKSON HAULMAAX/ULTIMAAX - 10.50"
RIDE HEIGHT
54 INCH AXLE SPACING
HENDRICKSON HN, HAULMAAX AND ULTIMAAX
SERIES STEEL BEAMS WITH BAR PIN

Description

FORE/AFT AND TRANSVERSE CONTROL RODS
REAR SHOCK ABSORBERS - TWO AXLES
(TANDEM)

Brake System

WABCO 4S/4M ABS WITHOUT TRACTION CONTROL
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER
WABCO OIL COALESCING FILTER FOR AIR DRYER
AIR DRYER MOUNTED OUTBOARD ON RH RAIL
STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME

Wheelbase & Frame

5200MM (205 INCH) WHEELBASE
7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT
BODY COMPANY INSTALLED ADDITIONAL FRONT FRAME REINFORCEMENT FOR SNOW PLOW
1475MM (58 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH
24 INCH INTEGRAL FRONT FRAME EXTENSION

Description

CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
123.78 in
CALCULATED EFFECTIVE BACK OF CAB TO
REAR SUSPENSION C/L (CA) : 120.78 in
CALC'D FRAME LENGTH - OVERALL : 314.69
CALC'D SPACE AVAILABLE FOR DECKPLATE :
123.78 in
CALCULATED FRAME SPACE LH SIDE : 38.66 in
CALCULATED FRAME SPACE RH SIDE : 73.54 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CROSSMEMBER BACK OF
TRANSMISSION
SNOWPLOW STEEL C-CHANNEL BACK OF CAB
MIDSHIP #1 CROSSMEMBER
STANDARD REAR MOST CROSSMEMBER
HEAVY DUTY SUSPENSION CROSSMEMBER
STANDARD WEIGHT REAR SUSPENSION
CROSSMEMBER

Chassis Equipment

14 INCH CHROMED STEEL BUMPER
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS
HUCK-SPIN ROUND COLLAR CHASSIS
FASTENERS

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
LH
25 INCH DIAMETER FUEL TANK(S)
PLAIN ALUMINUM/PAINTED STEEL
FUEL/HYDRAULIC TANK(S) WITH POLISHED
STAINLESS STEEL BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
CHROME FUEL TANK CAP(S)
DAVCO 482 FUEL/WATER SEPARATOR WITH 12
VOLT PREHEATER
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON
FUEL LINE
NO FUEL COOLER

Description

Tires

MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL
FRONT TIRES
MICHELIN XDE M/S 11R24.5 16 PLY RADIAL
REAR TIRES

Hubs

CONMET PRESET PLUS IRON FRONT HUBS
CONMET PRESET PLUS IRON REAR HUBS

Wheels

ALCOA LVL ONE 82462X 22.5X12.25 10-HUB
PILOT 4.68 INSET 10-HAND ALUMINUM DISC
FRONT WHEELS
ALCOA LVL ONE 98363X 24.5X8.25 10-HUB
PILOT ALUMINUM DISC REAR WHEELS
FRONT WHEEL MOUNTING NUTS
REAR WHEEL MOUNTING NUTS
NYLON WHEEL GUARDS FRONT AND REAR ALL
INTERFACES

Cab Exterior

110 INCH BBC STEEL CONVENTIONAL CAB
WESTERN STAR STAINLESS STEEL CAB SKIRT
AIR CAB MOUNTS WITH CHECK VALVE
NONREMOVABLE BUGSCREEN MOUNTED
BEHIND GRILLE
FRONT FENDERS
2 INCH FENDER EXTENSIONS
LH AND RH EXTERIOR GRAB HANDLES WITH
RUBBER INSERT AND LH AND RH INTERIOR
GRAB HANDLES MOUNTED TO A POST
STATIONARY BRIGHT FINISH GRILLE
CHROME HOOD MOUNTED AIR INTAKE GRILLE
GALVANEALD STEEL SEVERE SERVICE CAB
FIBERGLASS HOOD WITH ACCESS HATCHES
DUAL HADLEY SD-978 26 INCH RECTANGULAR
AIR HORNS
SINGLE ELECTRIC HORN
DUAL HORN SHIELDS
DOORS AND IGNITION KEYED THE SAME
REAR LICENSE PLATE MOUNT END OF FRAME
DUAL AMBER LED CLASS I STROBE LIGHTS
WITH STAINLESS STEEL BRACKETS

Description

SINGLE RECTANGULAR SEALED BEAM HEADLIGHTS WITH BRIGHT BEZELS
LED CHROME BULLET MARKER LIGHTS
WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH SINGLE CONNECTION AT LH FORWARD
DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH
LED SPOTLIGHT IN LH DOOR POST
INTEGRAL STOP/TAIL/BACKUP LIGHTS
STANDARD FRONT TURN SIGNAL LAMPS
DUAL MEKRA AERO BRIGHT FINISH HEATED DUAL AXIS 1-PIECE MOTORIZED MIRRORS WITH LIGHTS, LH AND RH REMOTE AND INTEGRAL CONVEX MIRRORS
CAB MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
DUAL MEKRA BRIGHT FINISH HEATED CONVEX MIRRORS WITH MANUAL ADJUSTMENT AND DUAL AXIS FOR 1-PIECE PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER
STAINLESS STEEL EXTERIOR SUN VISOR
17.5X35 INCH TINTED REAR WINDOW
TINTED DOOR GLASS
RH AND LH ELECTRIC POWERED WINDOWS
LOWER RH DOOR WINDOW WITH FRESNEL LENS
2-PIECE TINTED CURVED GASKET MOUNTED HEATED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, MOUNTED UNDER CAB, WITH REMOTE FILL

Cab Interior

SMOKY MOUNTAIN GRAY VINYL PREMIUM INTERIOR
BLACK HARD TRIM
PREMIUM LEFT HAND DOOR TRIM WITH CHERRY ACCENT
PREMIUM RIGHT HAND DOOR TRIM WITH CHERRY ACCENT

Description

BLACK MATS WITH DOUBLE INSULATION
DASH MOUNTED ASH TRAY AND LIGHTER,
DRIVER SIDE
FORWARD ROOF MOUNTED CONSOLE
PASSENGER SIDE WING DASH MOUNTED
GLOVE BOX WITH LOCKING DOOR
14"X7.75" DOCUMENT POUCH MOUNTED ON
BACK WALL BETWEEN SEATS
LH AND RH DOOR MAP POCKETS
COAT HOOK ON RH BACKWALL OF CAB
(1) DOUBLE CUP HOLDER WITH CELL PHONE
HOLDER LH OR RH DASH
TWO-TONE CHARCOAL UPPER/COOL GRAY
LOWER SOFT TOUCH WING DASH WITH BLACK
DRIVER SIDE COSMETIC UNDER DASH COVER
STANDARD WIRING
2-1/2 LB. FIRE EXTINGUISHER MOUNTED
OUTBOARD OF DRIVER SEAT
HEATER, DEFROSTER AND AIR CONDITIONER
WITH CONSTANT TEMPERATURE CONTROL
AND COSMETIC COVER
HVAC DUCTING WITH FOAM MAIN FRESH AIR
FILTER AND OUTSIDE PRE-FILTER
MAIN HVAC CONTROLS WITH RECIRCULATION
SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER
COMPRESSOR
RADIATOR MOUNTED AIR CONDITIONER
CONDENSER
BINARY CONTROL, R-134A
CAB INSULATION
AUTOMATIC SELF-RESET CIRCUIT BREAKER IN
MAIN DASH POWER DISTRIBUTION BOX AND
CIRCUIT BREAKER/FUSE IN AUXILIARY POWER
DISTRIBUTION BOXES
DOOR ACTIVATED DOME LIGHT, UNDER DASH
LIGHT AND LH AND RH DOOR MOUNTED
COURTESY LIGHTS
CAB DOOR LATCHES WITH MANUAL DOOR
LOCKS
(1) 12 VOLT POWER SUPPLY IN DASH

Description

PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER

PREMIUM HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER

INBOARD DRIVER AND PASSENGER SEAT ARMRESTS

BLACK MORDURA CLOTH DRIVER SEAT COVER

BLACK MORDURA CLOTH PASSENGER SEAT COVER

3 POINT HIGH VISIBILITY ORANGE RETRACTOR DRIVER AND PASSENGER SEAT BELTS

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

2-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL(S)

DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

NON-ADJUSTABLE SUSPENDED PEDALS

STAR GAUGES WITH BRIGHT BEZELS

FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH DRIVER INSTRUMENT PANEL

FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH CENTER INSTRUMENT PANEL

LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM

2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS

97 DB BACKUP ALARM

CRUISE CONTROL SWITCHES IN THE CENTER PANEL

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

DATASTAR DRIVER DISPLAY AND WARNING LAMP/LIGHT BAR DISPLAY, NON-DATA LINKED

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH

Description

2 INCH ELECTRIC FUEL GAUGE
FUEL FILTER RESTRICTION INDICATOR
EMISSIONS LIMITED IDLE ADJUST
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
ENGINE OIL TEMPERATURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
OUTSIDE AIR TEMPERATURE GAUGE WITH FAHRENHEIT AND CELSIUS DISPLAY MOUNTED IN OVERHEAD CONSOLE
(1) DASH MOUNTED PTO SWITCH WITH INDICATOR LAMP
ELECTRIC ENGINE OIL PRESSURE GAUGE
AM/FM/WB RADIO WITH BLUETOOTH AND MICROPHONE, FRONT USB PORT, FRONT AND REAR AUXILIARY INPUTS AND J1939
ROOF/OVERHEAD CONSOLE MOUNTED RADIO
(4) RADIO SPEAKERS IN CAB
POWER AND GROUND WIRING FOR CB RADIO IN OVERHEAD CONSOLE
MULTI-BAND AM/FM/WB/CB LH MIRROR MOUNTED ANTENNA SYSTEM
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITH ODOMETER
STANDARD VEHICLE SPEED SENSOR
ELECTRONIC 3000 RPM TACHOMETER
DETROIT CONNECT VIRTUAL TECHNICIAN CONNECTIVITY PACKAGE (DETROIT ENGINES ONLY)
5 YEARS TOTAL VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE (3 YEARS ADDITIONAL TO STANDARD)
IGNITION SWITCH CONTROLLED ENGINE STOP
SIX IGNITION CONTROLLED EXTRA SWITCHES WITH INDICATOR LIGHT, 10 AMPS, WIRED BETWEEN DRIVER AND PASSENGER SEATS
BW TRACTOR PROTECTION VALVE
TRAILER HAND CONTROL BRAKE VALVE
2 INCH VOLTMETER
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY AND ARCTIC TYPE BLADES

Description

CAB MARKER LIGHT AND HEADLIGHT SWITCH WITH SEPARATE SWITCH AND TERMINALS FOR CUSTOMER FURNISHED SNOW PLOW LIGHTS AND TURN SIGNALS

TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR

SELF CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITH BRAKE OVERRIDE

PACIFIC INSIGHT ELECTRONIC FLASHER

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: HSB906856 MED
MAROON PPG BASE/CLEAR

CAB INTERIOR PAINTED SAME AS CAB COLOR

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS