

**Mini-Bid T16060014****Three (3) 2016 or Newer Ford (or equal) F-350 XL Crew Cab 4x4 Chassis w/ Utility Body, Plow all Standard Features and Select Options (or equal)**

Exterior Color: Safety Yellow

Interior Color: Dark Matching

**Chassis**

XL 158" Wheelbase Styleside
GVW – 10,400 lbs. (min)
Front Axle 4,800 lbs. (min)
Rear Axle 6,800 lbs. (min)

**Powertrain**

6.2L 3-Valve SOHC EFI Triton V-8 (or equal)
Flex-fuel (E85) capable
Electronic 6 Speed Automatic Transmission
Axle, Limited slip (Ratio 3.73)

**Standard Equipment**

Seats – Front, Vinyl 40/20/40 Split Bench
Seats – Rear, Vinyl 60/40 Fold up Bench
Fuel tank – 35 gallon
Audio – AM/FM Stereo, Digital Clock, Two Speaker
Powerpoint –auxiliary 2, instrument panel mounted

**Selected Options**

Tough Bed (Spray-in Bedliner)
6" Angular Black Molded in Color Running Boards
LT245/75Rx17E BSW/ AT (5) Tires
Trailer Brake Controller
4X4 Electronic Shift-On-the-Fly
Upfitter Switches (4)
SYNC Basic
Steering Wheel Audio Controls
Tow Package w/ electronic brake controller

**Additional Option Items**

OEM backup camera or aftermarket rear vision camera system w/ 5" monitor
Audible Beep, frame mounted back up alarm
Fire extinguisher 10BC (min) cab mounted, secured with a quick release strap type clip
D.O.T. approved roadside triangle kit
4 complete sets of keys
Rust protections, including undercoating
Utility Body Knapheide 680J, Omaha-Standard 80V for 40" C.A. (or equal)
H.D. Anti-Skid Coating to be applied to interior floor of utility body and any outside area where there is footing

Marker Lights - Low profile Hi-Count LED light fixtures. Grote model G1903/ G1902 (or equal)
Rear mud flaps installed
License Plate Bracket – Illuminated type with armored lens. Signal Stat 9365W (or equal)
Telescopic roof – A two stage locking telescopic roof to cover load space.
Ladder Rack – Overhead type to be used in conjunction with telescopic roof. H.D. (1" dia) bow type w/retainer ears (2 sets) Mounted to front and rear of body using bolt on brackets w/ interior reinforcements
Security Bar – Hinged, dropdown security bar, operable from the ground level. W. retainers. To enclose all utility compartments.
At any point where cab or body access is provided, an adequate number of and size of grab handles, steps, footholds, etc., must be provided to assure safe movement.
Plow – H.D. 8' Plow assembly. To include all controls, valves lights, hoses, attachments, with cab mounted controls. (i.e. Meyer Model C-8 (or equal)

Delivery Instructions:

Metro-North Railroad Automotive Department  
 1 Croton Point Ave, Building #8  
 Croton-on-Hudson, NY 10520  
 Tel: (917) 271-1819  
 24 hour notice of delivery required.