

2016 or newer Ram 5500 Tradesman Crew Cab (or Equal) w/ Dump Body, all Standard Features and Select Options

Exterior Color: Safety Yellow
Interior Color: Dark Matching

Chassis

XL 173.4" Wheelbase
GVW – 16,500 lbs. (min)
Front Axle 4,600 lbs. (min)
Rear Axle 8,600 lbs. (min)
60" Cab to Axle Ratio (min)

Powertrain

6.7 Liter I6 Cummins Turbo Diesel Engine
Fuel – Diesel
Aisin Heavy Duty 6-Speed Automatic Transmission
Rear Axle Ratio 4.44
Transmission Power Take-Off System
Dual Rear Wheels

Standard Equipment

Seats - Heavy Duty Vinyl
Fuel tank – 52 gallon (min)

Selected Options

Black Tubular Side Steps
225/70R19.5G for all position tires
Full Size Spare Tire
19.5" x 6.0" Steel Wheels
Upfitter Switches (4)
Engine Block Heater
Radio 3.0
Heavy Duty Front Suspension Group
Tow Package w/ electronic brake controller
Parksense Rear Park Assist System
Parkview Rear Back Up Camera

Additional Option Items

Audible Beep, frame mounted back up alarm
Fire extinguisher 10BC (min) cab mounted, secured with a quick release strap type clip
D.O.T. approved roadside triangle kit
4 complete sets of keys

Dump Body and Up-Fit

Crysteel S-Tipper stainless steel dump body (or equal) Dimensions – Length 8' (min), Outside/Inside Width 78"/87" (min), Side Height 14" (min), Tailgate Height 20" (min) , 2.2 yard capacity (min)

MTA Metro-North Railroad

SPEC# 4H

Hoist – Crysteel , Lo-Boy B-5 (NTEA) Class B (or equal)
Roll up cargo cover stored in cab shield
Hydraulic system of sufficient capacity to operate all hydraulic functions of vehicle without overheating. Tank to be mounted to truck frame, painted black and labeled “hydraulic oil only”. Tank to contain full flow filter
H.D. Chrome plated shafts w/ safety check valves
Hoses – High pressure , wire braided, safety factor min 4 to 1. Bundles and secured, protected against chaffing.
Dump body controls mounted in cab
Tool Boxes - Behind cab, Street Side - Knapheide TB-24 (or equal) / Curb Side – Knapheide TB-30 (or equal) . Mounted to frame rails.
Two rung rigid stirrup steps with gripstrut mounted on body ahead of rear wheels on each side
An auxiliary step- lined with grip strut to be attached to recess in dump body side panel above bottom rail and stirrup steps.
Holland PH-T-60-AL (or equal) 10,000 lbs. MGTW , 2,000 lbs. vertical load w/ 7 pin trailer socket
Safety Chain Eyes - 5 ton capacity
License Plate Bracket – Illuminated type with armored lens. Signal Stat 9365W (or equal)
Marker Lights - Low profile Hi-Count LED light fixtures. Grote model G1903/ G1902 (or equal)
Rear mud flaps installed
Rust protections, including undercoating

Delivery Instructions:

Metro-North Railroad Automotive Department
1 Croton Point Ave, Building #8
Croton-on-Hudson, NY 10520
Tel: (917) 271-1819
24 hour notice of delivery required.