

**Mini-Bid #T16090028**  
**Niagara Frontier Transportation Authority**  
**(1) Ford F-550 XL or Equivalent Super Duty Chassis w/Omaha Standard Service**  
**Body or approved equal**

(Ref No. 4623)

An approved equal vehicle that meets the specifications will also be considered.

All dimensions referred to in the specifications are approximate. The vehicle must meet the following minimum requirements:

**3.1 Chassis:**

- 2016 or 2017
- Engine: 6.7L 4V OHV Diesel
- Transmission: TorqShift 6-Speed Automatic or equivalent
- Super Duty
- Regular Cab
- Limited Slip with a 4.88 axle ratio
- GVWR: 19,500 lb. Payload Plus Upgrade Package
- Tires: 225/70Rx19.5G BSW Traction
- Wheels: 19.5" Argent Painted Steel
- Four-Wheel Drive
- Heavy Duty Vinyl 40/20/40 Split Bench Seat
- Monotone Paint Application (oxford white)
- 165" Wheelbase
- Dual Rear Wheel
- XL Appearance package or equivalent
- XL Décor Group or equivalent
- Power Equipment Group or equivalent (power windows / power locks)
- Snow Plow Prep Package
- High Capacity Trailer Tow Package
- Low Deflection Package: Includes 2-inch spacer blocks. Recommended for rear-biased loading, such as wrecker/retriever applications.
- 4x4 Electronic-Shift-on-the-Fly (ESOF)
- Engine Block Heater
- Transmission Power Take-Off Provision
- Operator Command Regeneration (OCR)
- Trailer Brake Controller
- 6" Angular Black Molded-in-color Running Boards

- Rear View Camera and Prep Kit (fleet)
- Radio: AM/FM Stereo
- Cruise Control
- 50-State Emissions System
- 11' Omaha Standard/Palfinger ([www.palfinger.com](http://www.palfinger.com)) Service Body or equivalent with Rear Step Work Bench, vise ready
- Must be fitted with up-fitter switches within the cab

### 3.2 **Body:**

- One (1) new Omaha Standard Service body model: 132D54V, or approved equal, including the following standard equipment:

#### **Body Dimensions:**

- 132 inches overall length
- 95 ¾ inches overall width
- 84 inches front of body to center line of wheel opening
- 40 inches overall height
- 26 inches tread plate floor to top of side compartment
- 54 inches floor width between compartments
- 20 inches compartment depth
- 1466 lbs. standard weight plus options

#### **Body Features:**

- Entire body made of 14-gauge A-40 two sided galvanized zinc-coated steel
- Complete automotive type undercoating
- Die-formed distinctive large automotive style wheel well opening for large application tires and body rigidity

#### **Flooring:**

- 10-gauge steel tread-plate with rain holes a base of bulkhead

#### **Body Substructure:**

- 7-gauge steel channel front and rear cross members
- 10-gauge intermediate cross members
- 4-14-gauge floor stiffeners interlaced with cross members giving added strength in critical areas at rear of body

#### **Compartment Clear Opening Dimensions:**

- One (1) each side at front of body 27 ¾" W x 34" H
- One (1) each side intermediate compartment 19 ¾" W x 34" H
- One (1) each side over wheel well openings 43 ½" L x 14" H
- One (1) each side at rear of body 23 ¾" W x 34" H

**Compartments:**

- Trays must be constructed of 14-gauge galvanized steel, including four (4) divider trays for the front vertical compartments, 20 tray dividers, and one (1) shelf in each rear vertical compartment. All shelves and tray are adjustable. Compartment interiors must be factory painted grey for improved visibility in low light conditions.

**Doors:**

- Doors must be of double panel construction, exclusive rigid honeycomb polystyrene stiffeners bonded between panels for maximum stiffness. Hinges must be bolt on rod and bearing type, stainless steel hinge pins, bearing blocks and adjustable striker post.

**Lighting:**

- LED Light in every compartment, wired to up-fitter switch

**Bumper:**

- Constructed of 12-gauge galvanized steel with vise mount

**Electrical:**

- Automotive 12-volt, one (1) pair stop turn and tail at rear, and one (1) pair clear lens backup light, wired to truck chassis

**Warranty:**

- Six (6) year on hinges, latches, and rust through; three (3) year on all other body components

**Body Finish:**

- Painted Fleet white

**Rear Hitch:**

- Class V 2" rear receiver hitch with a 7-way RV-Style electrical connector

**Install:**

- The following items shall be installed and included with the vehicle: body, bumper, all legal lighting, fuel mill, mud flaps, supplies, paint, rear hitch, and 7-way connector.

## **1. PRICING**

The unit price bid must include delivery costs. Manuals may be furnished in an electronic format and must be furnished at the time of vehicle delivery.

## **2. DELIVERY**

The vehicle shall be delivered during normal business hours between 8:00 am and 3:00 pm EST to the Buffalo Niagara International Airport:

**Certificate of Origin/Title:** The certificate of origin or title shall be made out to NFTA, and accompany the vehicle when delivery is made.

Niagara Frontier Transportation Authority  
181 Ellicott Street  
Buffalo, NY 14203