S P E C I F I C A T I O N P R O P O S A L

	Description
Price Level	
	WESTERN STAR 4700 PRL-14T (EFF:10/05/15)
Data Version	
	SPECPRO21 DATA RELEASE VER 025
Vehicle Configuration	
	4700 SET-FORWARD FRONT AXLE CHASSIS
	2017 MODEL YEAR SPECIFIED
	SET FORWARD AXLE - TRUCK
	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK
	LH PRIMARY STEERING LOCATION
General Service	
	TRUCK/TRAILER CONFIGURATION
	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	CONSTRUCTION SERVICE
	GOVERNMENT BUSINESS SEGMENT
	DIRT/SAND/ROCK COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	WESTERN STAR VOCATIONAL WARRANTY
	EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs
	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 66000.0 lbs

	Description
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs
Truck Service	
	FRONT PLOW/END DUMP BODY
Tractor Service	
	FLATBED TRAILER
	SINGLE (1) TRAILER
Engine	
	DETROIT DD13 12.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1850 LB/FT @ 975 RPM
Electronic Parameters	
	65 MPH ROAD SPEED LIMIT
	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT
	10 MINUTES IDLE SHUTDOWN WITH CLUTCH AND SERVICE BRAKE OVERRIDE
	10 MINUTES PTO SHUTDOWN WITH CLUTCH AND BRAKE OVERRIDE
	PTO MODE ENGINE RPM LIMIT - 1100 RPM
	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED
	PTO RPM WITH CRUISE SET SWITCH - 800 RPM
	PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM
	ONE REMOTE PTO SPEED
	REMOTE PTO SPEED 1 SETTING - 900 RPM
	SOFT CRUISE CONTROL ENABLED
	PTO MINIMUM RPM - 600
	ENABLE AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE
Engine Equipment	
	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION
	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)
	NO 2013 ENGINE ESCALATOR
	STANDARD OIL PAN
	ENGINE MOUNTED OIL CHECK AND FILL
	ONE PIECE VALVE COVER

Description
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER WITH SAFETY ELEMENT AND INSIDE/OUTSIDE AIR WITH SNOW DOOR
DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES
BATTERY BOX FRAME MOUNTED
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE
AIR COMPRESSOR DISCHARGE LINE
ELECTRONIC ENGINE INTEGRAL WARNING AND DERATE PROTECTION SYSTEM
JACOBS COMPRESSION BRAKE
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH
10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT
STANDARD CURVE BRIGHT UPPER STACK(S)
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP
13 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING
NON-POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD
HORTON 2-SPEED DRIVEMASTER POLAREXTREME FAN DRIVE

	Description
	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR
	FULL FLOW OIL FILTER
	1500 SQUARE INCH ALUMINUM RADIATOR
	MOUNTING FOR FIREWALL MOUNTED SURGE TANK
	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES
	HDEP VARIABLE SPEED COOLANT PUMP AND NO OPTIONAL RADIATOR DRAIN VALVE
	PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER
	NO OIL PREHEATER
	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR
	ALUMINUM FLYWHEEL HOUSING
	DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH
Transmission	
	ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION
Transmission Equipment	
	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV
	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES
	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
	ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR, BLUNT CUT, MOUNTED BETWEEN DRIVER AND PASSENGER SEATS

Description
CUSTOMER INSTALLED CHELSEA 277 SERIES PTO
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED
TRANSMISSION PROGNOSTICS - ENABLED 2013
WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)
Front Axle and Equipment
DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE
BENDIX ADB22X-V AIR DISC FRONT BRAKES
NON-ASBESTOS FRONT BRAKE LINING
FRONT DISC BRAKE ROTORS
FRONT BRAKE DUST SHIELDS
SKF SCOTSEAL PLUS XL FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
STANDARD SPINDLE NUTS FOR ALL AXLES
FRONT AIR DISC BRAKE INTERNAL ADJUSTERS
STANDARD KING PIN BUSHINGS
TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR
POWER STEERING PUMP
4 QUART POWER STEERING RESERVOIR
OIL/AIR POWER STEERING COOLER
SYNTHETIC 75W-90 FRONT AXLE LUBE
Front Suspension
20,000# FLAT LEAF FRONT SUSPENSION
THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION
FRONT SHOCK ABSORBERS
Rear Axle and Equipment

	Description
	RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE
	4.89 REAR AXLE RATIO
	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING
	MXL 18N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES
	MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES
	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
	INDICATOR LIGHT FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH
	BENDIX ADB22X-V AIR DISC REAR BRAKES
	NON-ASBESTOS REAR BRAKE LINING
	STANDARD BRAKE CHAMBER LOCATION
	REAR DISC BRAKE ROTORS
	REAR BRAKE DUST SHIELDS
	SKF SCOTSEAL PLUS XL REAR OIL SEALS
	AIR DISC LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS
	REAR AIR DISC BRAKE INTERNAL ADJUSTERS
	SYNTHETIC 75W-90 REAR AXLE LUBE
Rear Suspension	
	HENDRICKSON HAULMAAX REAR SUSPENSION @ 46,000#
	HENDRICKSON HAULMAAX/ULTIMAAX - 10.50" RIDE HEIGHT
	54 INCH AXLE SPACING
	HENDRICKSON HN, HAULMAAX AND ULTIMAAX SERIES STEEL BEAMS WITH BAR PIN
	FORE/AFT AND TRANSVERSE CONTROL RODS
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)
Brake System	
	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL

	Description
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
	FIBER BRAID PARKING BRAKE HOSE
	STANDARD BRAKE SYSTEM VALVES
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
	WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER
	WABCO OIL COALESCING FILTER FOR AIR DRYER
	AIR DRYER MOUNTED OUTBOARD ON RH RAIL
	STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION
	PULL CABLES ON ALL AIR RESERVOIR(S)
Trailer Connections	
	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS
	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME
Wheelbase & Frame	
	5200MM (205 INCH) WHEELBASE
	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT
	BODY COMPANY INSTALLED ADDITIONAL FRONT FRAME REINFORCEMENT FOR SNOW PLOW
	1475MM (58 INCH) REAR FRAME OVERHANG
	FRAME OVERHANG RANGE: 51 INCH TO 60 INCH
	24 INCH INTEGRAL FRONT FRAME EXTENSION
	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 123.78 in
	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 120.78 in
	CALC'D FRAME LENGTH - OVERALL : 314.69
	CALC'D SPACE AVAILABLE FOR DECKPLATE : 123.78 in

	Description
	CALCULATED FRAME SPACE LH SIDE : 38.66 in
	CALCULATED FRAME SPACE RH SIDE : 73.54 in
	SQUARE END OF FRAME
	STANDARD WEIGHT ENGINE CROSSMEMBER
	STANDARD CROSSMEMBER BACK OF TRANSMISSION
	SNOWPLOW STEEL C-CHANNEL BACK OF CAB MIDSHIP #1 CROSSMEMBER
	STANDARD REARMOST CROSSMEMBER
	HEAVY DUTY SUSPENSION CROSSMEMBER
	STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER
Chassis Equipment	
	14 INCH CHROMED STEEL BUMPER
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE
	FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS
	HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS
Fuel Tanks	
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
	25 INCH DIAMETER FUEL TANK(S)
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS
	FUEL TANK(S) FORWARD
	PLAIN STEP FINISH
	CHROME FUEL TANK CAP(S)
	DAVCO 482 FUEL/WATER SEPARATOR WITH 12 VOLT PREHEATER
	EQUIFLO INBOARD FUEL SYSTEM
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
	NO FUEL COOLER
Tires	
	MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES
	MICHELIN XDE M/S 11R24.5 16 PLY RADIAL REAR TIRES
Hubs	
	CONMET PRESET PLUS IRON FRONT HUBS

	Description
	CONMET PRESET PLUS IRON REAR HUBS
Wheels	
	ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS
	ALCOA LVL ONE 98363X 24.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS
	FRONT WHEEL MOUNTING NUTS
	REAR WHEEL MOUNTING NUTS
	NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES
Cab Exterior	
	110 INCH BBC STEEL CONVENTIONAL CAB
	WESTERN STAR STAINLESS STEEL CAB SKIRT
	AIR CAB MOUNTS WITH CHECK VALVE
	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE
	FRONT FENDERS
	2 INCH FENDER EXTENSIONS
	LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERT AND LH AND RH INTERIOR GRAB HANDLES MOUNTED TO A POST
	STATIONARY BRIGHT FINISH GRILLE
	CHROME HOOD MOUNTED AIR INTAKE GRILLE
	GALVANEALED STEEL SEVERE SERVICE CAB
	FIBERGLASS HOOD WITH ACCESS HATCHES
	DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
	SINGLE ELECTRIC HORN
	DUAL HORN SHIELDS
	DOORS AND IGNITION KEYED THE SAME
	REAR LICENSE PLATE MOUNT END OF FRAME
	DUAL AMBER LED CLASS I STROBE LIGHTS WITH STAINLESS STEEL BRACKETS
	SINGLE RECTANGULAR SEALED BEAM HEADLIGHTS WITH BRIGHT BEZELS
	LED CHROME BULLET MARKER LIGHTS
	WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH SINGLE CONNECTION AT LH FORWARD
	DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH

Description
LED SPOTLIGHT IN LH DOOR POST
INTEGRAL STOP/TAIL/BACKUP LIGHTS
STANDARD FRONT TURN SIGNAL LAMPS
DUAL MEKRA AERO BRIGHT FINISH HEATED DUAL AXIS 1-PIECE MOTORIZED MIRRORS WITH LIGHTS, LH AND RH REMOTE AND INTEGRAL CONVEX MIRRORS
CAB MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
DUAL MEKRA BRIGHT FINISH HEATED CONVEX MIRRORS WITH MANUAL ADJUSTMENT AND DUAL AXIS FOR 1-PIECE PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER
STAINLESS STEEL EXTERIOR SUN VISOR
17.5X35 INCH TINTED REAR WINDOW
TINTED DOOR GLASS
RH AND LH ELECTRIC POWERED WINDOWS
LOWER RH DOOR WINDOW WITH FRESNEL LENS
2-PIECE TINTED CURVED GASKET MOUNTED HEATED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, MOUNTED UNDER CAB, WITH REMOTE FILL
Cab Interior
SMOKY MOUNTAIN GRAY VINYL PREMIUM INTERIOR
BLACK HARD TRIM
PREMIUM LEFT HAND DOOR TRIM WITH CHERRY ACCENT
PREMIUM RIGHT HAND DOOR TRIM WITH CHERRY ACCENT
BLACK MATS WITH DOUBLE INSULATION
DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE
FORWARD ROOF MOUNTED CONSOLE
PASSENGER SIDE WING DASH MOUNTED GLOVE BOX WITH LOCKING DOOR
14"X7.75" DOCUMENT POUCH MOUNTED ON BACK WALL BETWEEN SEATS
LH AND RH DOOR MAP POCKETS

Description
COAT HOOK ON RH BACKWALL OF CAB
(1) DOUBLE CUP HOLDER WITH CELL PHONE HOLDER LH OR RH DASH
TWO-TONE CHARCOAL UPPER/COOL GRAY LOWER SOFT TOUCH WING DASH WITH BLACK DRIVER SIDE COSMETIC UNDER DASH COVER
STANDARD WIRING
2-1/2 LB. FIRE EXTINGUISHER MOUNTED OUTBOARD OF DRIVER SEAT
HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT TEMPERATURE CONTROL AND COSMETIC COVER
HVAC DUCTING WITH FOAM MAIN FRESH AIR FILTER AND OUTSIDE PRE-FILTER
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR
RADIATOR MOUNTED AIR CONDITIONER CONDENSER
BINARY CONTROL, R-134A
CAB INSULATION
AUTOMATIC SELF-RESET CIRCUIT BREAKER IN MAIN DASH POWER DISTRIBUTION BOX AND CIRCUIT BREAKER/FUSE IN AUXILIARY POWER DISTRIBUTION BOXES
DOOR ACTIVATED DOME LIGHT, UNDER DASH LIGHT AND LH AND RH DOOR MOUNTED COURTESY LIGHTS
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS
(1) 12 VOLT POWER SUPPLY IN DASH
PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER
PREMIUM HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION,FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER
INBOARD DRIVER AND PASSENGER SEAT ARMRESTS
BLACK MORDURA CLOTH DRIVER SEAT COVER

Description
BLACK MORDURA CLOTH PASSENGER SEAT COVER
3 POINT HIGH VISIBILITY ORANGE RETRACTOR DRIVER AND PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN
2-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL(S)
DRIVER AND PASSENGER INTERIOR SUN VISORS
Instruments & Controls
NON-ADJUSTABLE SUSPENDED PEDALS
STAR GAUGES WITH BRIGHT BEZELS
FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH DRIVER INSTRUMENT PANEL
FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH CENTER INSTRUMENT PANEL
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS
97 DB BACKUP ALARM
CRUISE CONTROL SWITCHES IN THE CENTER PANEL
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
DATASTAR DRIVER DISPLAY AND WARNING LAMP/LIGHT BAR DISPLAY, NON-DATA LINKED
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE
FUEL FILTER RESTRICTION INDICATOR
EMISSIONS LIMITED IDLE ADJUST
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
ENGINE OIL TEMPERATURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
OUTSIDE AIR TEMPERATURE GAUGE WITH FAHRENHEIT AND CELSIUS DISPLAY MOUNTED IN OVERHEAD CONSOLE

	Description
	(1) DASH MOUNTED PTO SWITCH WITH INDICATOR LAMP
	ELECTRIC ENGINE OIL PRESSURE GAUGE
	AM/FM/WB RADIO WITH BLUETOOTH AND MICROPHONE, FRONT USB PORT, FRONT AND REAR AUXILIARY INPUTS AND J1939
	ROOF/OVERHEAD CONSOLE MOUNTED RADIO
	(4) RADIO SPEAKERS IN CAB
	POWER AND GROUND WIRING FOR CB RADIO IN OVERHEAD CONSOLE
	MULTI-BAND AM/FM/WB/CB LH MIRROR MOUNTED ANTENNA SYSTEM
	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITH ODOMETER
	STANDARD VEHICLE SPEED SENSOR
	ELECTRONIC 3000 RPM TACHOMETER
	DETROIT CONNECT VIRTUAL TECHNICIAN CONNECTIVITY PACKAGE (DETROIT ENGINES ONLY)
	5 YEARS TOTAL VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE (3 YEARS ADDITIONAL TO STANDARD)
	IGNITION SWITCH CONTROLLED ENGINE STOP
	SIX IGNITION CONTROLLED EXTRA SWITCHES WITH INDICATOR LIGHT, 10 AMPS, WIRED BETWEEN DRIVER AND PASSENGER SEATS
	BW TRACTOR PROTECTION VALVE
	TRAILER HAND CONTROL BRAKE VALVE
	2 INCH VOLTMETER
	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY AND ARCTIC TYPE BLADES
	CAB MARKER LIGHT AND HEADLIGHT SWITCH WITH SEPARATE SWITCH AND TERMINALS FOR CUSTOMER FURNISHED SNOW PLOW LIGHTS AND TURN SIGNALS
	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
	SELF CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITH BRAKE OVERRIDE
	PACIFIC INSIGHT ELECTRONIC FLASHER
Design	
	PAINT: ONE SOLID COLOR
Color	

Description
CAB COLOR A: HSB906856 MED MAROON PPG BASE/CLEAR
CAB INTERIOR PAINTED SAME AS CAB COLOR
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

* Must Be NYS Certified WBE to Bid